



# Jefferson County (KY) VOC Chart

Mobile Equipment Refinishing Operations

Regulation 7.79

In Effect: 5/1/1995

**ENVIROBASE®**  
HIGH PERFORMANCE

| Coating Category                               | lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts). |                                             |
|------------------------------------------------|---------------------------------------------------------------------|---------------------------------------------|
| Solvent (Surface Cleaner)*                     | 1.7 (200)                                                           | *VOC content applies to this category only. |
| Pre-Treatment Wash Primer                      | 6.5 (780)                                                           |                                             |
| Primer Surfacer                                | 4.8 (576)                                                           |                                             |
| Primer Sealer                                  | 4.6 (552)                                                           |                                             |
| Single Stage Coating                           | 5.0 (600)                                                           |                                             |
| Multi Stage Coating (2 Stage - BC/CC)          | 5.0 (600)                                                           |                                             |
| Multi Stage Coating (3 or more Stages - BC/CC) | 5.2 (624)                                                           |                                             |
| Specialty Coatings                             | 7.0 (840)                                                           |                                             |

| Product Code & Name                                    | Hardener/<br>Activator | Reducer | Mix Ratio | VOC Content                  |
|--------------------------------------------------------|------------------------|---------|-----------|------------------------------|
| <b>Solvent (Surface Cleaner)</b>                       |                        |         |           | Limit: 1.7 lbs/gal (200 g/L) |
| SU4901 Clean and Scuff Sponge                          | -                      | -       | -         | 0.06                         |
| SWX350 H <sub>2</sub> O-SO-CLEAN® Wax & Grease Remover | -                      | -       | -         | 0.17 (20)                    |
| SX394 1.4 Low VOC Cleaner                              | -                      | -       | -         | 1.34 (161)                   |

| Product Code & Name                                          | Hardener/Activator | Reducer                | Additives | Mix Ratio   | Applied VOC<br>Less Water Less Exempt                    |
|--------------------------------------------------------------|--------------------|------------------------|-----------|-------------|----------------------------------------------------------|
| <b>Pre-Treatment Coatings</b>                                |                    |                        |           |             | Limit: 6.5 lbs/gal (780 g/L)                             |
| SX2071 Etch Primer                                           | SX2072             | -                      | -         | 2:1         | 2.05 (246)                                               |
| SXA1031 Etch Primer - Gray                                   | -                  | -                      | -         | Aerosol     | N/A                                                      |
| <b>Primer Surfacer</b>                                       |                    |                        |           |             | Limit 4.8 lbs/gal (576 g/L)                              |
| ECP35 High Production Surfacer                               | EH391, EH392       | ECRXX                  | -         | 4:1:1       | 1.71 (205)                                               |
| ECP35 High Production Surfacer                               | EH391, EH392       | ECRXX                  | SLV814    | 4:1:1:110%  | 1.67 (200)                                               |
| DPLV Low VOC Epoxy Primer                                    | DP401LV            | DT18XX                 |           | 2:1:1       | 1.16 (139)                                               |
| EPW115 Waterborne Speed Prim                                 | -                  | T494                   | -         | 1: 13%      | 0.72 (86)                                                |
| NCP450 Iso-Free Primer                                       | NCX455             | DT18Xx                 |           | 4:1:1       | 1.33 (174)                                               |
| <b>Primer Sealer (apply over previously coated surfaces)</b> |                    |                        |           |             | Limit: 4.6 lbs/gal (552 g/L)                             |
| ECS2X A-Chromatic LV Sealer                                  | EH391, EH392       | DT1845, DT1850, DT1855 |           | 4:1:1       | 2.05 (246)                                               |
| ECS8X A-Chromatic LV Sealer                                  | EH391, EH392       | ECRXX, DT18XX          |           | 4:1:1       | 2.07 (248)                                               |
| <b>Basecoat for Multi Stage Topcoat System</b>               |                    |                        |           |             | Limit <sup>1,2</sup> : 5.0 / 5.2 lbs/gal (600 / 624 g/L) |
| Envirobase High Performance Basecoat                         | -                  | T494                   | -         | 100:10      | 3.33 (399)                                               |
| Envirobase High Performance Basecoat                         | -                  | T494                   | -         | 100:20      | 3.38 (405)                                               |
| Envirobase High Performance Basecoat                         | -                  | T494                   | -         | 100:30      | 3.50 (420)                                               |
| Envirobase High Performance Basecoat                         | -                  | -                      | T492      | 100:10      | 2.78 (333)                                               |
| Envirobase High Performance Basecoat                         | -                  | T494                   | T492      | 100:10:10   | 3.24 (388)                                               |
| Envirobase High Performance Basecoat                         | -                  | T494                   | T492      | 100:20:10   | 3.28 (393)                                               |
| Envirobase High Performance Basecoat                         | -                  | T494                   | T492      | 100:30:10   | 3.28 (393)                                               |
| Envirobase High Performance Basecoat                         | T493               | T494                   | T492      | 100:5:10:10 | 3.21 (385)                                               |
| Envirobase High Performance Basecoat                         | T493               | T494                   | T492      | 100:5:20:10 | 3.24 (388)                                               |



# Jefferson County (KY) VOC Chart

Mobile Equipment Refinishing Operations

**Regulation 7.79**

**In Effect: 5/1/1995**

**ENVIROBASE®**  
**HIGH PERFORMANCE**

| Product Code & Name                             | Hardener/Activator | Reducer          | Additives | Mix Ratio                                                      | Applied VOC<br>Less Water Less Exempt |
|-------------------------------------------------|--------------------|------------------|-----------|----------------------------------------------------------------|---------------------------------------|
| <b>Basecoat for Multi Stage Topcoat System</b>  |                    | <b>Continued</b> |           | <b>Limit <sup>1,2</sup>: 5.0 / 5.2 lbs/gal (600 / 624 g/L)</b> |                                       |
| Envirobase High Performance Basecoat            | T493               | T494             | T492      | 100:5:30:10                                                    | 3.25 (389)                            |
| Envirobase High Performance Basecoat            | T493               | -                | T492      | 100:5:10                                                       | 2.81 (337)                            |
| <b>Underbody Coatings (Specialty)</b>           |                    |                  |           | <b>Limit: 7.0 lbs/gal (840 g/L)</b>                            |                                       |
| Internal Repair System                          | T581               | T494             | -         | 100:15:15                                                      | 3.08 (369)                            |
| Internal Repair System                          | T581               | T494             | -         | 100:15:20                                                      | 3.09 (370)                            |
| <b>Clearcoat for Multi Stage Topcoat System</b> |                    |                  |           | <b>Limit <sup>1,2</sup>: 5.0 / 5.2 lbs/gal (600 / 624 g/L)</b> |                                       |
|                                                 |                    |                  |           |                                                                |                                       |
| DC2000 Ultra Velocity Clearcoat                 | DCH2015            | DT15Xx           |           | 4:1:1                                                          | 4.17 (500)                            |
| DC3000 High Velocity Clearcoat                  | DCH30XX            | -                |           | 4:1                                                            | 3.83 (459)                            |
| DC4000 Velocity Premium Clearcoat               | DCH30XX            | -                |           | 4:1                                                            | 4.11 (492)                            |
| DC4125 <i>Ceramiclear</i>                       | DCH4126            | -                | -         | 2:1                                                            | 2.05 (246)                            |
| DC7020 Premium Glamour Speed Clearcoat          | DCX8               | DT15XX           | -         | 4:1:1                                                          | 3.80 (455)                            |
| EC520 En-V ® High Production Clearcoat          | ECH5075            | ECRXX            | -         | 3:1:1                                                          | 2.07 (248)                            |
| EC530 En-V Performance Clearcoa                 | ECH5075            | ECRXX            | -         | 3:1:1                                                          | 1.94 (232)                            |
| EC550 En-V Ultra Gloss Clearcoat                | ECH5075            | ECRXX            | -         | 3:1:1                                                          | 2.01 (241)                            |
| EC800 Ultra Fast 2.1 Clearcoat                  | ECH8075<br>ECH8075 | DT1855<br>ECA83  | -         | 4:1:1                                                          | 2.08 (249)                            |
|                                                 |                    |                  |           | 4:1:1                                                          | 1.90 (228)                            |
| EC5515 Low VOC Matte Clear                      | ECH5075            | ECRXX, DT1585    | -         | 3:1:1                                                          | 2.02 (242)                            |
| EC5517 Low VOC Semi-Gloss Clear                 | ECH5075            | ECRXX, DT1585    |           | 3:1:1                                                          | 2.02 (242)                            |
| VC5250 DITZLER® Satin Clear                     | VH7250             | DT18XX           | -         | 4:1:1.5                                                        | 1.86 (2.23)                           |
| VC5700 <i>Ditzler</i> Custom Clear              | VH7780, VH7795     | DT1855           | -         | 2:1:1                                                          | 2.08 (249)                            |
|                                                 |                    |                  |           |                                                                |                                       |

<sup>1</sup> The VOC limit on tri-coat & quad-coat multi-stage systems is 5.2 lbs/gal.  
<sup>2</sup> The VOC of the BC/CC system is determined by BC/CC composite calculation, where the VOC system = (VOC BC + VOC CC)/3 {as specifically required by air quality regulations}.

## Additional Products (listing not intended to be all inclusive)

|                                   |                                         |                                                 |
|-----------------------------------|-----------------------------------------|-------------------------------------------------|
| SU4985 Universal Flattening Agent | SU4901 Clean and Scuff Sponge           | SXA1044 High Build Flexible Surfacers (Aerosol) |
| DX73 Fisheye Eliminator           | SUA4903 Advanced Plastic Bond (Aerosol) | SXA1050 Plastic Adhesion Promoter (Aerosol)     |
| SL814 Universal Flexibilizer      | SWX100 Waterborne Gun Cleaner           | SX1047 High Build WB Flexible Surfacers         |
| SLV840 Uniform Finish Blender     | SXA840 Uniform Finish Blender (Aerosol) | SX1056 Flexible 2K Sealer                       |
| SLV898 Retarder                   | SXA1030 Black Guide Coat (Aerosol)      | SX1057 Flexible 2K Surfacers                    |
| SU570 AdPro                       | SXA1041 Bumper Black (Aerosol)          |                                                 |

This "Jefferson County (KY) VOC Chart / Regulation 7.79 (PPG *Envirobase* High Performance)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Jefferson County (KY) VOC Chart / Regulation 7.79 (PPG *Envirobase* High Performance)" wall chart does not include all currently compliant *Envirobase* High Performance products. The representative products listed are compliant with Regulation 7.79 VOC limits as of the date of this wall chart; however, subsequent changes in Regulation 7.79 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

The PPG logo, *Envirobase*, *CeramiClear*, *Ditzler*, *One Visit*, *En-V*, and *H<sub>2</sub>O-So-Clean* are trademarks of PPG Industries of Ohio, Inc.