

South Coast AQMD

Motor Vehicle and Mobile Equipment Non-Assembly Line Coating Operations

Rule 1151

| In Effect: 11/1/2024; Phase 1 05/01/2025



Delfleet® Evolution



Delfleet Essential®

| Coating Category | lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts). | |
|--|---|--|
| Solvent (Surface Cleaner)* | 0.21 (25) | |
| Pretreatment Coating | 6.5 (780) | |
| Primer / Primer Surfacer/ Epoxy Primer | 4.8 (580) | |
| Primer Sealer | 4.6 (550) | |
| Single Stage Coating | 5.0 (600) | |
| Color Coating | 3.5 (420) | |
| Tinted Mid-Coat | 6.3 (750) | |
| Underbody Coating | 3.6 (430) | |
| Clear Coating | 4.3 (520) | |
| Matte Clear Coating | 4.6 (550) | |
| Uniform Finish Coating | 4.5 (540) | |
| Adhesion Promoter | 7.0 (540) | |

| Product Code & Name | Hardener/Activator | Reducer | Mix Ratio | VOC Content |
|--|--------------------|---------------------|---------------------|---|
| Solvent (Surface Cleaner) | | | | Limit: 0.21 lbs/gal (25 g/L) |
| SWX350 H ₂ O-SO-CLEAN® Wax & Grease Remover | - | - | - | 0.19 (23) |
| SXA103 MULTI-PREP® | - | - | Aerosol | 5.88 (705) |
| SXA330 Wax and Grease Remover | - | - | Aerosol | 5.78 (693) |
| CFX435LV—Low VOC Cleaner | | Water | 1 : 1 | 0.20 (25) |
| Product Code & Name | Hardener/Activator | Reducer | Additives | Mix Ratio |
| Pre-Treatment Coatings | | | | Limit: 6.5 lbs/gal (780 g/L) |
| SXA1031 Etch Primer - Gray | - | - | - | Aerosol |
| Primer / Primer Surfacer / Epoxy Primer | | | | Limit 4.8 lbs/gal (580 g/L) |
| ESU410 2.1/2.8 Polyurethane Primer | ESU419 | - | ESX590 | 5:1+6 oz/RTS gal |
| ESU460/461/462 4.6 VOC Epoxy Primers | ESU469 | - | - | 2:1 |
| ESU470 2.1 VOC Wet on Wet Epoxy Primer—Gray | ESU479 | ESR300 or ESR310 | - | 2:1:1 or 2:1:2 (reducer is last) |
| ESU480/481/482 2.1 VOC Epoxy Primer | ESU489 | - | - | 4:1 |
| F3970 Ultra High Solids Primer—Gray | F3971 | F3385, F3390, F3395 | F3400 or F3405 | 3:1+6 oz/RTS gal + 10% optional reducer |
| F3975 Fast Dry Surfacer | F3270 | - | - | 3:1 |
| F3993/95/97 Conventional Epoxy Primers | F3996 | F33XX | - | 3:1:1/2 |
| F3998 2.1 VOC Primer Surfacer | F3999 | - | - | 2:1 |
| F4921/BK/WH 2.1 VOC Epoxy Primer | F4922 | F3385, F3390, F3395 | - | 3:1:1 |
| F4932 2.1 VOC Fast Dry Urethane Surfacer | F4933 | F3385, F3390, F3395 | - | 4:1:1 |
| F4935/36/37 High Solids Epoxy Primers | F4938 | - | - | 1:1 |
| F3985/86 Pigmented Sealers | F3260 | F33XX | F3400, F3405, F3410 | 3:1+6 oz/RTS gal + 1/2 optional reducer |
| F4943/BK 2.1 VOC Fast Dry Sealers | F4933 | F3385, F3390, F3395 | - | 3:1:1 |
| Red font indicates oxsol containing products for use through appropriate sell through periods | | | | |

South Coast AQMD

Motor Vehicle and Mobile Equipment Non-Assembly Line Coating Operations

Rule 1151

| In Effect: 11/1/2024; Phase 1 05/01/2025



Delfleet® Evolution



Delfleet Essential®

| Product Code & Name | Hardener/Activator | Reducer | Additives | Mix Ratio | Applied VOC Less Water Less Exempt |
|---|---|---|---------------------|--|---------------------------------------|
| Single Stage Coating | | | | | Limit: 5.0 lbs/gal (600 g/L) |
| ESSS Single Stage Polyurethane Enamel | ESH200 | - | ESX5XX | 6:1:1 | 2.80 (3.35) |
| FDG 5.0 VOC Single Stage Polyurethane Enamel (** Various Reducers available some may contain Oxsol or be higher in VOC) | F3270 | F33XX** | F3400, F3405, F3410 | 2:1:1/2 + 2 oz/RTS gallon (optional) | 5.00 (600) |
| FDGH Single Stage High Solids Polyurethane Enamel (** Various Reducers available some may contain Oxsol or be higher in VOC) | F3260 | F33XX** | F3400, F3405, F3410 | 3:1:6 oz/RTS gallon + 10% reducer | 3.42 (410) |
| FDGU Single Stage Ultra High Solids Polyurethane Enamel | F3260 | F3385, F3390, F3395 | F3400, F3405, F3410 | 3:1:6 oz/RTS gallon + 10% reducer | 2.82 (338) |
| FDSH High Solids Polyurethane Single Stage (** Various Reducers available some may contain Oxsol or be higher in VOC) | F3260 | F33XX (optional) | F3400, F3405, F3410 | 3:1:6 oz/RTS gallon + 10% reducer (optional) | 3.42 (410) |
| FDSU Ultra High Solids Polyurethane Single Stage | F3260 | F3385, F3390, F3395 (optional) | F3400, F3405, F3410 | 3:1:6 oz/RTS gallon + 10% reducer (optional) | 2.82 (338) |
| Basecoat for Multi Stage Topcoat System | | | | | Limit: 3.5 lbs/gal (420 g/L) |
| **Changes 11/1/2025 - Oxsol containing Color | | | | | |
| ESSS Basecoat | ESH210 | - | ESB800 | 2:1:1 | 3.04 (364) |
| FBCH High Solids Polyurethane Basecoat | F3240, F3259, F3260 | - | F3440, F3441, F3442 | 3:1:1 | 3.49 (419) |
| FBCS High Solids Polyurethane Basecoat—Fast | F3260 | F33XX** | - | 3:1 + 10% | 3.41 (408) |
| Clear Coating | | | | | Limit: 4.3 lbs/gal (520 g/L) |
| ESC621 2.1 VOC Urethane Clearcoat | ESH200 | ESR300, ESR310, ESX711, ESX721 | - | 4:1:2 4:1:1 | 2.04 (245) |
| ESC600 Urethane Clear | ESH200 | - | ESX5X0 | 6:1:1 | 4.07 (488) |
| F3906 High Build Polyurethane Clear | F3240, F3260 | F33XX | F3400, F3405, F3410 | 3:1:1/2 + 2 oz / | 3.40 (405) |
| F3921 2.1 VOC Clearcoat | F3210, F3211 | F3385, F3390, F3395 | - | 3:1:1/2 | 2.05 (246) |
| F3930 Conventional Clear | F3260 | F33XX | F3400, F3405, F3410 | 3:1:1+ optional 2 oz/RTS Gallon | 4.12 (494) |
| Additional Products (listing not intended to be all inclusive) | | | | | |
| FDGU500 FDGU Blending Clear | SU4901 Clean and Scuff Sponge | SLV73 Fisheye Eliminator | | | |
| FDGH500 FDGH Blending Clear | SUA4903 Advanced Plastic Bond (Aerosol) | SXA840 Uniform Finish Blender (Aerosol) | | | |
| Red font indicates oxsol containing products for use through appropriate sell through periods | | | | | |

This "South Coast AQMD Rule 1151 (PPG Delfleet Evolution and Delfleet Essential) wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "South Coast AQMD Rule 1151 (PPG Delfleet Evolution and Delfleet Essential) wall chart does not include all currently compliant products. The representative products listed are compliant with South Coast AQMD Rule 1151 VOC limits as of the date of this wall chart; however, subsequent changes in South Coast AQMD Rule 1151 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

©2025 PPG Industries, Inc. All rights reserved www.ppgrefinish.com

The PPG Logo, Delfleet, Delfleet Essential, H2O-So-Clean and Multi-Prep are registered trademarks of PPG Industries Ohio, Inc.

Table 1- Table of Standards
Regulatory VOC Content Limits and Effective Dates for Automotive Coatings

| Coating Categories | Current Limits ⁽¹⁾ | | Phase I Limits Effective November 1, 2024 | | Phase II Limits | | |
|---------------------------------|-------------------------------|--------|---|--------|-----------------|--------|----------------|
| | g/L | lb/gal | g/L | lb/gal | g/L | lb/gal | Effective Date |
| Base Coatings | | | | | | | |
| Color Coating ⁽²⁾ | 420 | 3.5 | | | 250 | 2.1 | 1/1/2030 |
| Tinted Mid-Coat | 420 | 3.5 | 750 | 6.3 | 250 | 2.1 | 1/1/2030 |
| Clear Coatings | | | | | | | |
| Gloss Clear Coating | 250 | 2.1 | 520 | 4.3 | 250 | 2.1 | 1/1/2030 |
| Matte Clear Coating | 250 | 2.1 | 550 | 4.6 | | | |
| Primers and Sealers | | | | | | | |
| Pretreatment Wash Primer | 660 | 5.5 | 780 | 6.5 | 660 | 5.5 | 1/1/2028 |
| Epoxy Primer | 250 | 2.1 | 580 | 4.8 | 340 | 2.8 | 1/1/2028 |
| Primer Sealer | 250 | 2.1 | 550 | 4.6 | 250 | 2.1 | 1/1/2029 |
| Primer Surfacer | 250 | 2.1 | 580 | 4.8 | 250 | 2.1 | 1/1/2029 |
| Other Coating Categories | | | | | | | |
| Adhesion Promoter | 540 | 4.5 | 840 | 7.0 | 720 | 6.0 | 1/1/2028 |
| Single-Stage Coating | 340 | 2.8 | 600 | 5.0 | 340 | 2.8 | 1/1/2028 |
| Temporary Protective Coating | 60 | 0.5 | | | | | |
| Truck Bed Liner Coating | 310 | 2.6 | | | | | |
| Underbody Coating | 430 | 3.6 | | | | | |
| Uniform Finishing Coating | 540 | 4.5 | | | | | |
| Any Other Coating Type | 250 | 2.1 | | | | | |

1 The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

2 See Paragraph (d)(4) for Color Coatings supplied in half-pint or smaller containers.

Table 4: pCBtF and t-BAc Prohibition Timeline

| Category | Prohibition Effective Date | Sell-through End Date | Use-through End Date |
|------------------------------|----------------------------|-----------------------|----------------------|
| Color Coatings | November 1, 2025 | November 1, 2026 | January 1, 2028 |
| All Other Coating Categories | May 1, 2025 | May 1, 2026 | July 1, 2027 |