



Washington DC
Mobile Equipment Repair and Refinishing
Chapter 20-7 Section 20-718
In Effect: 5/9/2016



Coating Category	lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).
Solvent (Surface Cleaner)*	0.21 (25)
Pretreatment Coating	5.5 (660)
Primer / Primer Surfacer	2.1 (250)
Primer Sealer	2.1 (250)
Single Stage Coating	2.8 (340)
Color Coating	3.5 (420)
Underbody Coating	3.6 (430)
Clear Coating	2.1 (250)
Adhesion Promoter	4.5 (540)

*VOC content applies to this category only

Product Code & Name	Hardener/ Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				Limit: 0.21 lbs/gal (25 g/L)
SWX350 H ₂ O-SO-CLEAN® Wax and Grease Remover	-	-	-	0.17 (20)
SX1009 2.9 VOC Bug and Tar Remover*	-	-	-	2.89 (346)
SX103 MULTI-PREP® **	-	-	-	6.47 (775)
SXA330 Wax and Grease Remover***	-	-	Aerosol	5.77 (691)

*4(a)(1),(2) & (3) allows 20 gal/yr. cleaning solvents if annual coatings usage greater than or equal to 400 gal., 15 gal/yr. if greater than or equal to 150 gal coatings annually and 10 gal/yr. if less than 150 gal. coatings annually
 **4(b) allows 20 gal/yr cleaning solvents for plastic solvents if dispensed in a non aerosol hand-held spray bottle
 ***4(c) allows 160 oz./day aerosol cleaning solvents

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings					Limit: 5.5 lbs/gal (660 g/L)
SX2071 Etch Primer	SX2072	-	-	2:1	2.05 (246)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer Surfacer					Limit 2.1 lbs/gal (250 g/L)
JP211 Gray Polyester Primer / Filler	MEKP	-	-	1 oz. per quart	1.36 (163)
JP35X 2.1 VOC Multi-Purpose Primer	JH358	JR55X	-	4:1:2	2.05 (246)
JP390 2.1 VOC Epoxy Primer - Gray	JH397	JR55X	-	2:1:1	2.07 (248)
Primer Sealer (apply over previously coated surfaces)					Limit: 2.1 lbs/gal (250 g/L)
JP35X 2.1 VOC Multi-Purpose Primer	JH358	JR55X	JC78x, or JC7200	3:1:1:1	2.09 (250)
JP36X Series 2.1 VOC Urethane Sealers	JH358	JR55X	-	4:1:1	2.09 (250)
JP390 2.1 VOC Epoxy Primer - Gray	JH397	JR55X	-	2:1:2	2.07 (248)
Single Stage Coating					Limit: 2.8 lbs/gal (340 g/L)
JTX 2.8 VOC Direct Gloss Acrylic Urethane	JH6028	JR55X	-	4:1:2	2.80 (335)
JLX 2.8 VOC Acrylic Enamel	JH6028	JR55X	-	4:1:1	2.76 (331)
Basecoat for Multi Stage Topcoat System					Limit: 3.5 lbs/gal (420 g/L)
JBX 3.5 Acrylic Basecoat	-	JR29X	-	1:1	3.48 (417)
Use JBPX blend to spray mix recommendation without JH6028 only with new color formulas that contain J179					
JBPX 3.5 VOC Acrylic Urethane Basecoat	-	JR55X	-	1:1	3.49 (419)
Use JBPX blend to spray mix recommendations with JH6028 with all historic color formulas that contain J136					
JBPX 3.5 VOC Acrylic Urethane Basecoat	JH6028	JR55X	-	10:1:10	3.48 (417)
JBPX 3.5 VOC Acrylic Urethane Basecoat	JH6028	JR55X	-	10:1:5	3.48 (417)



Washington DC
Mobile Equipment Repair and Refinishing
Chapter 20-7 Section 20-718
In Effect: 5/9/2016



Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Clear Coating					Limit: 2.1 lbs/gal (250 g/L)
JC830 2.1 VOC Production Clear	JH8370, JH8380, JH8390	JR555, JR556	-	4:1:0.5	2.08 (249)
JC7200 2.1 VOC European Clearcoat	JH72XX	-	-	2:1	2.08 (249)

Additional Products (listing not intended to be all inclusive)		
SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacers (Aerosol)
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SX1047 High Build WB Flexible Surfacers
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)	SU470LV 1K Compliant Adhesion Promoter
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)	

This "Washington DC Chapter 7 Section 718 (PPG Shop-Line)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Washington DC Chapter 7 Section 718 (PPG Shop-Line)" wall chart does not include all currently compliant Shop-Line products. The representative products listed are compliant with Washington DC Chapter 7 Section 718 VOC limits as of the date of this wall chart; however, subsequent changes in Washington DC Chapter 7 Section 718 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.