



Yolo-Solano AQMD

Motor Vehicle and Mobile Equipment Coating Operations

Rule 2.26

Amended: 12/10/2008 | In Effect: 7/1/2010

ENVIROBASE®
HIGH PERFORMANCE

Coating Category		lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).		
Solvent (Surface Cleaner)*		0.21 (25)	*VOC content applies to this category only	
Pretreatment Coating		5.5 (660)		
Primer / Primer Surfacer		2.1 (250)		
Primer Sealer		2.1 (250)		
Single Stage Coating		2.8 (340)		
Color Coating		3.5 (420)		
Underbody Coating		3.6 (430)		
Clear Coating		2.1 (250)		
Uniform Finish Coating		4.5 (540)		
Adhesion Promoter		4.5 (540)		

Product Code & Name	Hardener/Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				Limit: 0.21 lbs/gal (25 g/L)
SWX350 H ₂ O-SO-CLEAN® Wax & Grease Remover	-	-	-	0.17 (20)
SXA330 Wax and Grease Remover*			Aerosol	5.77 (691)
* Rule 2.31 section 113 limited exemption for cleaning with aerosol products up to 160 fluid ounces per day per facility and facility has a District permit or written exemption from the APCO.				
Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio
Pre-Treatment Coatings				Applied VOC Less Water Less Exempt
SX1071 ECOBASE® 5.5 Etch Prime	SX1072	-	-	1:1 5.48 (657)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol N/A
Primer Surfacer				Limit 2.1 lbs/gal (250 g/L)
ECP35 High Production Surfacer	EH391, EH392	ECRXX	-	4:1:1 1.71 (205)
ECP35 High Production Surfacer	EH391, EH392	ECRXX	SLV814	4:1:1:110% 1.67 (200)
DPLV Low VOC Epoxy Primer	DP401LV	DT18XX	-	2:1:1 1.16 (139)
EPW115 Waterborne Speed Prim	-	T494	-	1: 13% 0.72 (86)
NCP450 Iso-Free Primer	NCX455	DT18XX	-	4:1:1 1.33 (174)
Primer Sealer (apply over previously coated surfaces)				Limit: 2.1 lbs/gal (250 g/L)
ECS2X A-Chromatic LV Sealer	EH391, EH392	DT1845, DT1850, DT1855	-	4:1:1 2.05 (246)
ECS8X A-Chromatic LV Sealer	EH391, EH392	ECRXX, DT18XX	-	4:1:1 2.07 (248)
Basecoat for Multi Stage Topcoat System				Limit: 3.5 lbs/gal (420 g/L)
Envirobase High Performance Basecoat	-	T494	-	100:10 3.33 (399)
Envirobase High Performance Basecoat	-	T494	-	100:20 3.38 (405)
Envirobase High Performance Basecoat	-	T494	-	100:30 3.50 (420)
Envirobase High Performance Basecoat	-	-	T492	100:10 2.78 (333)
Envirobase High Performance Basecoat	-	T494	T492	100:10:10 3.24 (388)
Envirobase High Performance Basecoat	-	T494	T492	100:20:10 3.28 (393)
Envirobase High Performance Basecoat	-	T494	T492	100:30:10 3.28 (393)
Envirobase High Performance Basecoat	T493	T494	T492	100:5:10:10 3.21 (385)
Envirobase High Performance Basecoat	T493	T494	T492	100:5:20:10 3.24 (388)



Yolo-Solano AQMD

Motor Vehicle and Mobile Equipment Coating Operations

Rule 2.26

Amended: 12/10/2008 | In Effect: 7/1/2010

ENVIROBASE®
HIGH PERFORMANCE

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Basecoat for Multi Stage Topcoat System					Limit: 3.5 lbs/gal (420 g/L)
Envirobase High Performance Basecoat		T494T493	T492	100:5:30:10	3.25 (389)
Envirobase High Performance Basecoat	T493	-	T492	100:5:10	2.81 (337)
Envirobase High Performance Basecoat	T4900	-	-	100:20	3.27 (392)
Envirobase High Performance Basecoat	T4900	T595	-	100:5:15	3.1 (371)
Envirobase High Performance Basecoat	T4910	T595	-	100:20	3.3 (395)
Envirobase High Performance Basecoat	T4910	T595	-	100:5:15	3.1 (371)
Underbody Coatings (Specialty)					Limit: 3.6 lbs/gal (430 g/L)
Internal Repair System	T581	T494	-	100:15:15	3.08 (369)
Internal Repair System	T581	T494	-	100:15:20	3.09 (370)
Clearcoat for Multi Stage Topcoat System					Limit: 2.1 lbs/gal (250 g/L)
DC4125 CeramiClear	DCH4126	-	-	2:1	2.05 (246)
EC520 En-V® High Production Clearcoat	ECH5075	ECRXX	-	3:1:1	2.07 (248)
EC530 En-V Performance Clearcoat	ECH5075	ECRXX	-	3:1:1	1.94 (232)
EC550 En-V Ultra Gloss Clearcoat	ECH5075	ECRXX	-	3:1:1	2.01 (241)
EC800 Ultra Fast 2.1 Clearcoat	ECH8075 ECH8075	DT1855 ECA83	-	4:1:1 4:1:1	2.08 (249) 1.90 (228)
EC5515 Low VOC Matte Clear	ECH5075	ECRXX, DT1855	-	3:1:1	2.02 (242)
EC5517 Low VOC Semi-Gloss Clear	ECH5075	ECRXX, DT1855	-	3:1:1	2.02 (242)
VC5250 DITZLER® Satin Clear	VH7250	DT18XX	-	4:1:1.5	1.86 (2.23)
VC5700 Ditzler Custom Clear	VH7780, VH7795	DT1855	-	2:1:1	2.08 (249)

Additional Products (listing not intended to be all inclusive)

SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacer (Aerosol)
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SU470LV 1K Compliant Adhesion Promoter
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)	
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)	

This "Yolo-Solano AQMD Rule 2.26 PPG Envirobase High Performance" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Yolo-Solano AQMD Rule 2.26 PPG Envirobase High Performance" wall chart does not include all currently compliant PPG Envirobase High Performance products. The representative products listed are compliant with Yolo-Solano AQMD Rule 2.26 VOC limits as of the date of this wall chart; however, subsequent changes in Yolo-Solano AQMD Rule 2.26 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws, with all applicable federal, state and local laws.

The PPG logo, Envirobase, Multi-Prep, Ecobase, CeramiClear, En-V, Ditzler, One Visit and H₂O-So-Clean are trademarks of PPG Industries of Ohio, Inc.