Sacramento Metro AQMD

Automotive, Mobile Equipment and Associated Parts and Components
Coating Operations

Rule 459

Amended: 8/25/2011 | **In Effect: 2/29/2012**

Coating Category	lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).
Solvent (Surface Cleaner)*	0.21 (25)
Pretreatment Coating	5.5 (660)
Primer / Primer Surfacer	2.1 (250)
Primer Sealer	2.1 (250)
Single Stage Coating	2.8 (340)
Color Coating	3.5 (420)
Underbody Coating	3.6 (430)
Clear Coating	2.1 (250)
Uniform Finish Coating	4.5 (540)
Adhesion Promoter	4.5 (540)

*VOC content applies to this category only

Product Code & Name	Hardener/ Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				**Limit: 0.21 lbs/gal (25 g/L)**
SWX350 H_2O-SO-CLEAN® Wax & Grease Remover	-	-	-	0.17 (20)
SX1009 2.9 VOC Bug & Tar Remover*				2.89 (346)

*Allowed under Rule 459 Section 310.7 “a person shall not use any solvent other than bug and tar remover regulated under Consumer Products Regulation 94507”

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings					**Limit: 5.5 lbs/gal (660 g/L)**
SX2071 Etch Primer	SX2072			2:1	2.05 (246)
SXA1031 Etch Primer - Gray**	-	-	-	Aerosol	N/A
***Products regulated as aerosol coatings and subject to applicable MIR limits under the California Aerosol Coating Product Regulation (Title 17, CCR, Sections 94520–94528).*					
Primer Surfacer					**Limit 2.1 lbs/gal (250 g/L)**
QP-5x00 Low VOC Primer Surfacer	QH-3800	QR-29xx	-	4:1:2	1.0 (120)
QP-5x00 Low VOC Primer Surfacer	QH-3800	QR-29xx	SLV814	4:1:2:10%	0.94 (113)
Primer Sealer (apply over previously coated surfaces)					**Limit: 2.1 lbs/gal (250 g/L)**
QS-3x00 Low VOC Primer Sealer	QH-3800	QR-29xx		4:1:1	1.15 (138)
QS-3x00 Low VOC Primer Sealer	QH-3800	QR-29xx	SLV814	4:1:1:10%	1.08 (129)
Basecoat for Multi Stage Topcoat System					**Limit: 3.5 lbs/gal (420 g/L)**
QB Waterborne Basecoat	-	QR2960/QR2970	-	1:10%	0.77 (92)
QB Waterborne Basecoat	-	QR2960/QR2970	-	1:20%	0.72 (86)
QB Waterborne Basecoat	-	QR2960/QR2970	-	1:30%	0.68 (81)
Clearcoat for Multi Stage Topcoat System					**Limit: 4.3 lbs/gal (520 g/L)**
QC-4000 Low VOC Glamour Clear	QH-4x00	QR-29xx	-	3:1: ½	1.11 (132)
QC-9000 Low VOC Speed Clear	QH-9x00	-	-	4:1	1.08 (129)
QC-9000 Low VOC Speed Clear	QH-9x00	-	SL93LV	4:1:2%	1.06 (127)
QC-9000 Low VOC Speed Clear	QH-9x00	-	SLV814	3:1:½	0.97 (116)

© 2026 PPG Industries

Sacramento Metro AQMD

Automotive, Mobile Equipment and Associated Parts and Components Coating Operations

Rule 459

Amended: 8/25/2011 | **In Effect: 2/29/2012**

Additional Products ***(listing not intended to be all inclusive)***		
SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacer (Aerosol)
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SU470LV 1K Compliant Adhesion Promoter
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)	
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)	

This "Sacramento Metro AQMD Rule 459 PPG *Quickline* wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Sacramento Metro AQMD Rule 459 PPG *Quickline* wall chart does not include all currently compliant PPG *Quickline* products. The representative products listed are compliant with Sacramento Metro AQMD Rule 459 VOC limits as of the date of this wall chart; however, subsequent changes in Sacramento Metro AQMD Rule 459 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

The *PPG* logo, *Quickline*, *Multi-Prep*, and *H_2O-So-Clean* are trademarks of PPG Industries of Ohio, Inc.