

PRODUKT	CODE	SATAjet X		SATAjet X 5500		SATAmijinjet 4400 B		SATAjet 100 BF	
		HVLP	RP	HVLP	RP	HVLP	RP	HVLP	RP
PE Spritzfüller	P565-7100								P 2,0 bar
2K Haftgrund, chromatfrei	P565-9868		I Düse 1,3 2,0 bar	O Düse 1,3 2,0 bar	I Düse 1,4 2,0-2,2 bar				
2K EP Primer	P565-5225		I Düse 1,3 bis max. 2,0 bar		I Düse 1,3- 1,6 1,6-2,0 bar				
Self Levelling Primer	P565-5601/5/7		I Düse 1,3 2,0 bar		I Düse 1,2- 1,3 2,0-2,2 bar				
2K Premium Füller	P565-5701/5/7							1,6-1,8 2,0 bar	1,6-1,8 2,0 bar
2K Fast-Sand Primer	P565-5511/5/7							1,6-1,8 2,0 bar	1,6-1,8 2,0 bar
2K Eco Dry Primer	P565-5811/5/7							1,6-1,8 bis max. 2,0 bar	1,6-1,8 bis max. 2,0 bar
2K HS+ Decklacksystem	P471		I Düse 1,2-1,3 2,0 bar		I Düse 1,2- 1,3 2,0-2,2 bar		1,0-1,2 1,0-2,0 bar		
AQUABASE Plus Wasserbasislack	P989	O Düse 1,3 1,6-1,8 bar Nebelgang: 1,0-1,3 bar		O Düse 1,3 1,6-1,8 bar Nebelgang: 1,0-1,3 bar		1,2-1,4 1,0-2,0 bar Nebelgang: 1,0-1,3 bar			
AQUABASE PLUS inkl. OneVisit Converter	P950-9000 / P950-9100	I Düse 1,3 1,8 bar Nebelgang: 1,8 bar		I Düse 1,3 1,8 bar Nebelgang: 1,8 bar					
2K HS / HS+ Klarlacke	P190-6560 P190-6570 P190-7020 P190-8001		I Düse 1,2 2,0 bar		I Düse 1,2 2,0-2,2 bar		1,0-1,2 1,0-2,0 bar		
	P190-8000 P190-8002		I Düse 1,2 2,0 bar		I Düse 1,2 2,0-2,2 bar		1,0-1,2 1,0-2,0 bar		
2K Ceramic Klarlack	P190-6512		I Düse 1,2 2,0 bar		I Düse 1,2 2,0-2,2 bar		1,0-1,2 1,0-2,0 bar		
2K Mattklarlack System	P190-1062/1063	I Düse 1,3-1,4 1,8-2,0 bar		I Düse 1,3- 1,5 1,8 - 2,0 bar					

LACKIERPISTOLENEMPFEHLUNGEN - DEVILBISS

PRODUKT	CODE	GTI Pro LITE		DV1-B	DV1-C1	PRI Pro LITE	SRI Pro LITE	
		HVLP LK HV30	Transtech LK TE20	HVLP / Plus	HVLP / PLUS	Transtech PR10	HVLP HV5	Transtech TE5
PE Spritzfüller	P565-7100					2,5 2,0-2,5 bar		
2K Haftgrund, chromatfrei	P565-9868		1,3 2,0 bar					
2K EP Primer	P565-5225		1,3-1,6 2,0 bar					
Self Levelling Primer	P565-5601/5/7		1,3-1,4 2,0 bar					
2K Premium Füller	P565-5701/5/7					1,6-1,8 2,0-2,5 bar		
2K Fast-Sand Primer	P565-5511/5/7					1,6-1,8 2,0-2,5 bar		
2K Eco Dry Primer	P565-5811/5/7					1,6-1,8 bis max. 2,0 bar		
2K HS+ Decklacksystem	P471		1,3-1,4 2,0 bar				1,2-1,4 1,0-2,0 bar	1,2-1,4 1,0-2,0 bar
AQUABASE Plus Wasserbasislack	P989	1,3 1,6-1,8 bar Nebelgang: 1,0-1,3 bar		1,2B 1,8bar Nebelgang: 1,4bar /Silber grob 1,2bar			1,2-1,4 1,0-2,0 bar Nebelgang: 1,0-1,3 bar	1,2-1,4 1,0-2,0 bar Nebelgang: 1,0-1,3 bar
AQUABASE Plus Wasserbasislack inkl. OneVisit Converter	P950-9000 / P950-9100			1,2-1,3 1,5 bar Nebelgang: 1,5 bar				
2K HS / HS+ Klarlacke	P190-6560 P190-6570 P190-7020 P190-8000 P190-8001 P190-8002		1,2-1,3 2,0 bar		1,2-1,3 bis max. 1,6 bar		1,2-1,4 1,0-2,0 bar	1,2-1,4 1,0-2,0 bar
2K Ceramic Klarlack	P190-6512		1,2-1,3 2,0 bar		1,2-1,3 bis max. 1,6 bar		1,2-1,4 1,0-2,0 bar	1,2-1,4 1,0-2,0 bar
2K Mattklarlack System	P190-1062/1063	1,4 1,8 bar			1,3-1,4 bis max. 1,6 bar			

LACKIERPISTOLENEMPFEHLUNGEN - ANEST IWATA

PRODUKT	CODE	LS 400	WS 400	WS 400 evo clear	W-400 WBX	LS-400 entech	WS Primer	W-300 WB	LPH-80	AZ3 HTE2
		SERIE 2	SERIE 2	Compliant		HVLP	Füller	Smart Repair	Spot-Repair	HVLP
PE Spritzfüller	P565-7100									2,5 2,0 bar
2K Haftgrund, chromatfrei	P565-9868			1,3 HD 2,0 bar	1,3 2,0 bar					
2K EP Primer	P565-5225			1,4-1,5 HD 2,0 bar						
Self Levelling Primer	P565-5601/5/7			1,3-1,4 HD 2,0 bar	1,4 2,0 bar		1,3 bis max. 2,0 bar			
2K Premium Füller	P565-5701/5/7						1,6-1,8 bis max. 2,0 bar			
2K Fast-Sand Primer	P565-5511/5/7						1,6-1,8 bis max. 2,0 bar			
2K Eco Dry Primer	P565-5811/5/7						1,6 bis max. 2,0 bar			
2K HS+ Decklacksystem	P471		1,2-1,3 HD 2,0 bar	1,3-1,4 HD 1,8-2,0 bar	1,3-1,4 2,0 bar				1,2 1,0-1,2 bar	
AQUABASE Plus Wasserbasislack	P989	1,2-1,3 ETS 1,6-1,8 bar Nebelgang: 1,1-1,3 bar				1,3 ETS 1,6-1,8 bar Nebelgang: 1,0-1,3 bar		1,2 1,5 bar	1,2 1,0-1,2 bar Nebelgang: 0,8-1,0 bar	
AQUABASE Plus Wasserbasislack inkl. OneVisit Converter	P950-9000 / P950-9100	1,3 ET 1,8 bar Nebelgang: 1,8 bar								
2K HS / HS+ Klarlacke	P190-6560 P190-6570 P190-7020 P190-8000 P190-8001 P190-8002		1,2-1,3 HD 2,0 bar	1,3 HD 1,8-2,0 bar	1,3-1,4 2,0 bar			1,2 1,5 bar	1,2 1,0-1,2 bar	
2K Ceramic Klarlack	P190-6512		1,2-1,3 HD 2,0 bar	1,3 HD 2,0 bar					1,2 1,0-1,2 bar	
2K Mattklarlack System	P190-1062/1063	1,3-1,5 ETS 2,0 bar				1,3-1,5 ETS 1,8 bar			1,2 1,0-1,2 bar	

* Angaben in **fett/bold**: = primäre Empfehlung