



Placer County APCD

Automotive Refinishing Operations

Rule 234

Amended: 10/14/2010 | In Effect: 7/1/2011

ENVIROBASE®
HIGH PERFORMANCE

| Coating Category | | lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts). | | | |
|--|--|---|------------------------|-----------|---------------------------------------|
| Product Code & Name | | Hardener/Activator | Reducer | Mix Ratio | VOC Content |
| Solvent (Surface Cleaner)* | | 0.21 (25) | | | |
| Pretreatment Coating | | 5.5 (660) | | | |
| Primer / Primer Surfacer | | 2.1 (250) | | | |
| Primer Sealer | | 2.1 (250) | | | |
| Single Stage Coating | | 2.8 (340) | | | |
| Color Coating | | 3.5 (420) | | | |
| Underbody Coating | | 3.6 (430) | | | |
| Clear Coating | | 2.1 (250) | | | |
| Uniform Finish Coating | | 4.5 (540) | | | |
| Adhesion Promoter | | 4.5 (540) | | | |
| | | *VOC content applies to this category only | | | |
| Solvent (Surface Cleaner) | | Limit: 0.21 lbs/gal (25 g/L) | | | |
| SWX350 H ₂ O-SO-CLEAN® Wax & Grease Remover | | - | - | - | 0.17 (20) |
| SX1009 2.9 VOC Bug & Tar Remover* | | | | | 2.89 (346) |
| *Allowed under Rule 234 Section 305.4 "For solvents used for bug & tar removal, the VOC content shall meet a maximum limit of 40% volatile organic compound by weight" | | | | | |
| Product Code & Name | | Hardener/Activator | Reducer | Additives | Applied VOC Less Water Less Exempt |
| Pre-Treatment Coatings | | Limit: 5.5 lbs/gal (660 g/L) | | | |
| SX1071 ECOBASE® 5.5 Etch Prime | | SX1072 | | 1:1 | 5.48 (657) |
| SXA1031 Etch Primer - Gray | | - | - | Aerosol | N/A |
| Primer Surfacer | | Limit 2.1 lbs/gal (250 g/L) | | | |
| ECP35 High Production Surfacer | | EH391, EH392 | ECRXX | - | 4:1:1 1.71 (205) |
| ECP35 High Production Surfacer | | EH391, EH392 | ECRXX | SLV814 | 4:1:1:110% 1.67 (200) |
| DPLV 2.1 Low VOC Epoxy Primer | | DP401LV | DT18XX | | 2:1:1 1.16 (139) |
| EPW115 Waterborne Speed Prim | | - | T494 | - | 1: 13% 0.72 (86) |
| NCP450 Iso-Free Primer | | NCX455 | DT18XX | - | 4:1:1 1.33 (174) |
| Primer Sealer (apply over previously coated surfaces) | | Limit: 2.1 lbs/gal (250 g/L) | | | |
| ECS2X A-Chromatic LV Sealer | | EH391, EH392 | DT1845, DT1850, DT1855 | | 4:1:1 2.05 (246) |
| ECS8X A-Chromatic LV Sealer | | EH391, EH392 | ECRXX, DT18XX | | 4:1:1 2.07 (248) |
| Basecoat for Multi Stage Topcoat System | | Limit: 3.5 lbs/gal (420 g/L) | | | |
| Envirobase High Performance Basecoat | | - | T494 | - | 100:10 3.33 (399) |
| Envirobase High Performance Basecoat | | - | T494 | - | 100:20 3.38 (405) |
| Envirobase High Performance Basecoat | | - | T494 | - | 100:30 3.50 (420) |
| Envirobase High Performance Basecoat | | - | - | T492 | 100:10 2.78 (333) |
| Envirobase High Performance Basecoat | | - | T494 | T492 | 100:10:10 3.24 (388) |
| Envirobase High Performance Basecoat | | - | T494 | T492 | 100:20:10 3.28 (393) |
| Envirobase High Performance Basecoat | | - | T494 | T492 | 100:30:10 3.28 (393) |
| Envirobase High Performance Basecoat | | T493 | T494 | T492 | 100:5:10:10 3.21 (385) |
| Envirobase High Performance Basecoat | | T493 | T494 | T492 | 100:5:20:10 3.24 (388) |



Placer County APCD

Automotive Refinishing Operations

Rule 234

Amended: 10/14/2010 | **In Effect: 7/1/2011**

ENVIROBASE®
HIGH PERFORMANCE

| Product Code & Name | Hardener/Activator | Reducer | Additives | Mix Ratio | Applied VOC Less Water Less Exempt |
|---|--------------------|-----------------|-----------|----------------|---------------------------------------|
| Basecoat for Multi Stage Topcoat System | | | | | Limit: 3.5 lbs/gal (420 g/L) |
| Envirobase High Performance Basecoat | | T494T493 | T492 | 100:5:30:10 | 3.25 (389) |
| Envirobase High Performance Basecoat | T493 | - | T492 | 100:5:10 | 2.81 (337) |
| Envirobase High Performance Basecoat | T4900 | - | - | 100:20 | 3.27 (392) |
| Envirobase High Performance Basecoat | T4900 | T595 | - | 100:5:15 | 3.1 (371) |
| Envirobase High Performance Basecoat | T4910 | T595 | - | 100:20 | 3.3 (395) |
| Envirobase High Performance Basecoat | T4910 | T595 | - | 100:5:15 | 3.1 (371) |
| Underbody Coatings (Specialty) | | | | | Limit: 3.6 lbs/gal (430 g/L) |
| Internal Repair System | T581 | T494 | - | 100:15:15 | 3.08 (369) |
| Internal Repair System | T581 | T494 | - | 100:15:20 | 3.09 (370) |
| Clearcoat for Multi Stage Topcoat System | | | | | Limit: 2.1 lbs/gal (250 g/L) |
| DC4125 Ceramiclear | DCH4126 | | | 2:1 | 2.05 (246) |
| EC520 En-V® High Production Clearcoat | ECH5075 | ECRXX | | 3:1:1 | 2.07 (248) |
| EC530 En-V Performance Clearcoat | ECH5075 | ECRXX | | 3:1:1 | 1.94 (232) |
| EC550 En-V Ultra Gloss Clearcoat | ECH5075 | ECRXX | | 3:1:1 | 2.01 (241) |
| EC800 Ultra Fast 2.1 Clearcoat | ECH8075 ECH8075 | DT1855 ECA83 | | 4:1:1 4:1:1 | 2.08 (249) 1.90 (228) |
| EC5515 Low VOC Matte Clear | ECH5075 | ECRXX, DT1855 | | 3:1:1 | 2.02 (242) |
| EC5517 Low VOC Semi-Gloss Clear | ECH5075 | ECRXX, DT1855 | | 3:1:1 | 2.02 (242) |
| VC5250 DITZLER® Satin Clear | VH7250 | DT18XX | - | 4:1:1.5 | 1.86 (2.23) |
| VC5700 Ditzler Custom Clear | VH7780, VH7795 | DT1855 | - | 2:1:1 | 2.08 (249) |

Additional Products (listing not intended to be all inclusive)

| | | |
|------------------------------------|---|--|
| SLV4985 Universal Flattening Agent | SU4901 Clean and Scuff Sponge | SXA1044 High Build Flexible Surfacer (Aerosol) |
| SLV73 Fisheye Eliminator | SUA4903 Advanced Plastic Bond (Aerosol) | SXA1050 Plastic Adhesion Promoter (Aerosol) |
| SLV814 Universal Flexibilizer | SWX100 Waterborne Gun Cleaner | SX1047 High Build WB Flexible Surfacer |
| SLV840 Uniform Finish Blender | SXA840 Uniform Finish Blender (Aerosol) | SXA1041 Bumper Black (Aerosol) |
| SLV898 Retarder | SXA1030 Black Guide Coat (Aerosol) | SU470LV 1K Compliant Adhesion Promoter |

This "Placer County APCD Rule 234 PPG Envirobase High Performance" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Placer County APCD Rule 234 PPG Envirobase High Performance" wall chart does not include all currently compliant PPG Envirobase High Performance products. The representative products listed are compliant with Placer County APCD Rule 234 VOC limits as of the date of this wall chart; however, subsequent changes in Placer County APCD Rule 234 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

The PPG logo, Envirobase, Ecobase, CeramiClear, En-V, Ditzler, One Visit and H₂O-So-Clean are trademarks of PPG Industries of Ohio, Inc.