



State of Indiana
Automotive Refinishing Coatings
Title 326, Article 8, Rule 10
Amended 3/27/2009 In Effect: 6/1/2009

ENVIROBASE®
HIGH PERFORMANCE

PPG DELTRON®NXT

Coating Category	lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).	
Surface Preparation (Cleaner) -Plastic*	6.5 (780)	
Surface Preparation (Cleaner) - Other*	1.4 (168)	
Pretreatment Wash Primer	6.5 (780)	
Primer / Primer Surfacer	4.8 (576)	
Primer Sealer	4.6 (552)	
Single Stage Coating	5.0 (600)	
Multi-Stage Coating (2 Stage—BC/CC)	5.0 (600)	
Multi-Stage Coating (3 or more Stages—BC/CC)	5.2 (624)	
Specialty Coating	7.0 (840)	

*VOC content applies to this category only

Product Code & Name	Hardener/ Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner) Limit: 6.5 / 1.4 lbs/gal (780 / 168 g/L)				
SWX350 H ₂ O-SO-CLEAN® Wax & Grease Remover	-	-	-	0.17 (20)
SX103 MULTI-PREP® (Plastic only)				6.49 (778)
SX394 1.4 Low VOC Cleaner				1.34 (161)

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings Limit: 6.5 lbs/gal (780 g/L)					
SX2071 Etch Primer	SX2072			2:1	2.05 (246)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer Surfacer Limit: 4.8 lbs/gal (576 g/L)					
ECP35 High Production Surfacer	EH391, EH392	ECRXX	-	4:1:1	1.71 (205)
ECP35 High Production Surfacer	EH391, EH392	ECRXX	SLV814	4:1:1:110%	1.67 (200)
DPLV Low VOC Epoxy Primer	DP401LV	DT18XX		2:1:1	1.16 (139)
EPW115 Waterborne Speed Prime	-	T494	-	1: 13%	0.72 (86)
NCP450 Iso-Free Primer	NCX455	DT18Xx		4:1:1	1.33 (174)

Primer Sealer (apply over previously coated surfaces) Limit: 4.6 lbs/gal (552 g/L)					
ECS2X A-Chromatic LV Sealer	EH391, EH392	DT1845, DT1850, DT1855		4:1:1	2.05 (246)
ECS8X A-Chromatic LV Sealer	EH391, EH392	ECRXX, DT18XX		4:1:1	2.07 (248)

Basecoat for Multi Stage Topcoat System Limit: 5.0 / 5.2 lbs/gal (600 624 g/L)					
Envirobase High Performance Basecoat	-	T494	-	100:10	3.33 (399)
Envirobase High Performance Basecoat	-	T494	-	100:20	3.38 (405)
Envirobase High Performance Basecoat	-	T494	-	100:30	3.50 (420)
Envirobase High Performance Basecoat	-	-	T492	100:10	2.78 (333)
Envirobase High Performance Basecoat	-	T494	T492	100:10:10	3.24 (388)
Envirobase High Performance Basecoat	-	T494	T492	100:20:10	3.28 (393)
Envirobase High Performance Basecoat	-	T494	T492	100:30:10	3.28 (393)
Envirobase High Performance Basecoat	T493	T494	T492	100:5:10:10	3.21 (385)
Envirobase High Performance Basecoat	T493	T494	T492	100:5:20:10	3.24 (388)



State of Indiana
Automotive Refinishing Coatings
Title 326, Article 8, Rule 10
Amended 3/27/2009 In Effect: 6/1/2009

ENVIROBASE®
HIGH PERFORMANCE

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Basecoat for Multi Stage Topcoat System				Limit: 5.0 / 5.2 lbs/gal (600 / 624 g/L)	
Envirobase High Performance Basecoat		T494T493	T492	100:5:30:10	3.25 (389)
Envirobase High Performance Basecoat	T493	-	T492	100:5:10	2.81 (337)
Envirobase High Performance Basecoat	T4900	-	-	100:20	3.27 (392)
Envirobase High Performance Basecoat	T4900	T595	-	100:5:15	3.1 (371)
Envirobase High Performance Basecoat	T4910	T595	-	100:20	3.3 (395)
Envirobase High Performance Basecoat	T4910	T595	-	100:5:15	3.1 (371)
Underbody Coatings (Specialty)				Limit: 7.0 lbs/gal (840 g/L)	
Internal Repair System	T581	T494	-	100:15:15	3.08 (369)
Internal Repair System	T581	T494	-	100:15:20	3.09 (370)
Clearcoat for Multi Stage Topcoat System				Limit: 5.0 / 5.2 lbs/gal (600 624 g/L)	
DC2000 Ultra Velocity Clearcoat	DCH2015	DT15Xx		4:1:1	4.17 (500)
DC3000 High Velocity Clearcoat	DCH30XX	-		4:1	3.83 (459)
DC4000 Velocity Premium Clearcoat	DCH30XX	-		4:1	4.11 (492)
DC4125 <i>Ceramiclear</i>	DCH4126	-	-	2:1	2.05 (246)
DC7020 Premium Glamour Speed Clearcoat	DCX8	DT15XX	-	4:1:1	3.80 (455)
EC520 En-V ® High Production Clearcoat	ECH5075	ECRXX	-	3:1:1	2.07 (248)
EC530 En-V Performance Clearcoa	ECH5075	ECRXX	-	3:1:1	1.94 (232)
EC550 En-V Ultra Gloss Clearcoat	ECH5075	ECRXX	-	3:1:1	2.01 (241)
EC800 Ultra Fast 2.1 Clearcoat	ECH8075 ECH8075	DT1855 ECA83	-	4:1:1 4:1:1	2.08 (249) 1.90 (228)
EC5515 Low VOC Matte Clear	ECH5075	ECRXX, DT1585	-	3:1:1	2.02 (242)
EC5517 Low VOC Semi-Gloss Clear	ECH5075	ECRXX, DT1585		3:1:1	2.02 (242)
VC5250 DITZLER® Satin Clear	VH7250	DT18XX	-	4:1:1.5	1.86 (2.23)
VC5700 <i>Ditzler</i> Custom Clear	VH7780, VH7795	DT1855	-	2:1:1	2.08 (249)

1 The VOC limit on tri-coat & quad-coat multi-stage systems is 5.2 lbs/gal.

2 The VOC of the BC/CC system is determined by BC/CC composite calculation, where the VOC system = (VOC BC + VOC CC)/3 {as specifically required by air quality regulations.

Additional Products (listing not intended to be all inclusive)

SU4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacers (Aerosol)
DX73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)
SL814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SX1056 Flexible 2K Sealer
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)	SX1057 Flexible 2K Surfacers
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)	SU570 AdPro

We strongly recommend that distributors and body shop facility operators review Indiana Title 326 Article 8 Rule 10 for all requirements listed, including those above and beyond what is contained in this document. In particular, the rule should be consulted for distributor record keeping requirements (326 IAC 8-10-6 (b) including point of sale documentation), and body shop work standards (326 IAC 8-10-5), painter training requirements (326 IAC 8-10-5 (d)) and recordkeeping requirements for spray activity (326 IAC 8-10-9). A copy of the rule can be obtained from Indiana DEM <https://in.gov/indem/airquality/2422.htm> Select Auto Refinishing Rule 326 IAC 8-10 [PDF], then scroll down to Rule 10. PPG Refinish can provide a copy if necessary.

This "Indiana VOC Chart Title 326 Article 8 Rule 10 PPG Envirobase High Performance" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Indiana VOC Chart Title 326 Article 8 Rule 10 PPG Envirobase High Performance" wall chart does not include all currently compliant PPG Envirobase High Performance products. The