



# Utah R307-354

## Automotive Refinish Coatings

Applies to Box Elder, Cache, Davis, Salt Lake, Tooele, Utah and Weber counties. Before September 1, 2018, applies to operations that have the potential to emit (PTE) 2.7 tons/year or more of VOC, including related cleaning activities. Effective September 1, 2018, R307-354 shall apply to an automotive refinishing operation that uses a combined 20 gallons or more of coating products and associated solvents/year.



Amended: 12/6/2017 | In Effect: 9/1/2018

| Coating Category         | lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts). |
|--------------------------|---|
| Pretreatment Coating     | 5.5 (660)   |
| Primer / Primer Surfacer | 2.1 (250)   |
| Primer Sealer            | 2.1 (250)   |
| Single Stage Coating     | 2.8 (340)   |
| Color Coating            | 3.5 (420)   |
| Underbody Coating        | 3.6 (430)   |
| Clear Coating            | 2.1 (250)   |
| Uniform Finish Coating   | 4.5 (540)   |
| Adhesion Promoter        | 4.5 (540)   |

\*VOC content applies to this category only

| Product Code & Name   | Hardener/Activator | Reducer | Mix Ratio | VOC Content |
|---|--------------------|---------|-----------|-------------|
| <b>Solvent (Surface Cleaner)</b>                                      |                    |         |           | Limit: n/a  |
| SWX350 H <sub>2</sub> O-SO-CLEAN <sup>®</sup> Wax and Grease Remover* | -                  | -       | -         | 0.17 (20)   |
| SX1009 2.9 VOC Bug and Tar Remover*                                   | -                  | -       | -         | 2.89 (346)  |
| SX103 MULTI-PREP <sup>®</sup> *                                       | -                  | -       | -         | 6.49 (778)  |
| SX330 Wax and Grease Remover*   | -                  | -       | -         | 6.36 (762)  |
| SX394 1.4 Low VOC Cleaner*  | -                  | -       | -         | 1.34 (161)  |

| Product Code & Name   | Hardener/Activator | Reducer | Additives        | Mix Ratio       | Applied VOC<br>Less Water Less Exempt |
|---|--------------------|---------|------------------|-----------------|---------------------------------------|
| <b>Pre-Treatment Coatings</b>   |                    |         |                  |                 | Limit: 5.5 lbs/gal (660 g/L)          |
| SX1071 ECOBASE <sup>®</sup> 5.5 Etch Prime  | SX1072             | -       | -                | 1:1             | 5.48 (657)                            |
| SXA1031 Etch Primer - Gray  | -                  | -       | -                | Aerosol         | N/A                                   |
| <b>Primer Surfacer</b>  |                    |         |                  |                 | Limit 2.1 lbs/gal (250 g/L)           |
| JP211 Gray Polyester Primer / Filler  | MEKP               | -       | -                | 1 oz. per quart | 1.36 (163)                            |
| JP35X 2.1 VOC Multi-Purpose Primer  | JH358              | JR55X   | -                | 4:1:2           | 2.05 (246)                            |
| JP390 2.1 VOC Epoxy Primer - Gray   | JH397              | JR55X   | -                | 2:1:1           | 2.07 (248)                            |
| <b>Primer Sealer (apply over previously coated surfaces)</b>  |                    |         |                  |                 | Limit: 2.1 lbs/gal (250 g/L)          |
| JP35X 2.1 VOC Multi-Purpose Primer  | JH358              | JR55X   | JC78x, or JC7200 | 3:1:1:1         | 2.09 (250)                            |
| JP36X Series 2.1 VOC Urethane Sealers   | JH358              | JR55X   | -                | 4:1:1           | 2.09 (250)                            |
| JP390 2.1 VOC Epoxy Primer - Gray   | JH397              | JR55X   | -                | 2:1:2           | 2.07 (248)                            |
| <b>Single Stage Coating</b>   |                    |         |                  |                 | Limit: 2.8 lbs/gal (340 g/L)          |
| JTX 2.8 VOC Direct Gloss Acrylic Urethane   | JH6028             | JR55X   | -                | 4:1:2           | 2.80 (335)                            |
| JLX 2.8 VOC Acrylic Enamel  | JH6028             | JR55X   | -                | 4:1:1           | 2.76 (331)                            |
| <b>Basecoat for Multi Stage Topcoat System</b>  |                    |         |                  |                 | Limit: 3.5 lbs/gal (420 g/L)          |
| JBX 3.5 Acrylic Basecoat  | -                  | JR29X   | -                | 1:1             | 3.48 (417)                            |
| <i>Use JBPX blend to spray mix recommendation without JH6028 only with new color formulas that contain J179</i>   |                    |         |                  |                 |                                       |
| JBPX 3.5 VOC Acrylic Urethane Basecoat  | -                  | JR55X   | -                | 1:1             | 3.49 (419)                            |
| <i>Use JBPX blend to spray mix recommendations with JH6028 with all historic color formulas that contain J136</i> |                    |         |                  |                 |                                       |
| JBPX 3.5 VOC Acrylic Urethane Basecoat  | JH6028             | JR55X   | -                | 10:1:10         | 3.48 (417)                            |
| JBPX 3.5 VOC Acrylic Urethane Basecoat  | JH6028             | JR55X   | -                | 10:1:5          | 3.48 (417)                            |



# Utah R307-354

## Automotive Refinish Coatings

Applies to Box Elder, Cache, Davis, Salt Lake, Tooele, Utah and Weber counties. Before September 1, 2018, applies to operations that have the potential to emit (PTE) 2.7 tons/year or more of VOC, including related cleaning activities. Effective September 1, 2018, R307-354 shall apply to an automotive refinishing operation that uses a combined 20 gallons or more of coating products and associated solvents/year.

Amended: 12/6/2017 | In Effect: 9/1/2018



| Product Code & Name               | Hardener/Activator     | Reducer      | Additives | Mix Ratio | Applied VOC<br>Less Water Less Exempt |
|-----------------------------------|------------------------|--------------|-----------|-----------|---------------------------------------|
| <b>Clear Coating</b>              |                        |              |           |           | <b>Limit: 2.1 lbs/gal (250 g/L)</b>   |
| JC830 2.1 VOC Production Clear    | JH8370, JH8380, JH8390 | JR555, JR556 | -         | 4:1:0.5   | 2.08 (249)                            |
| JC7200 2.1 VOC European Clearcoat | JH72XX                 | -            | -         | 2:1       | 2.08 (249)                            |

| <b>Additional Products (listing not intended to be all inclusive)</b> |   |   |
|---|---|---|
| SLV4985 Universal Flattening Agent                                    | SU4901 Clean and Scuff Sponge           | SXA1044 High Build Flexible Surfacers (Aerosol) |
| SLV73 Fisheye Eliminator  | SUA4903 Advanced Plastic Bond (Aerosol) | SXA1050 Plastic Adhesion Promoter (Aerosol)     |
| SLV814 Universal Flexibilizer   | SWX100 Waterborne Gun Cleaner           | SX1047 High Build WB Flexible Surfacers         |
| SLV840 Uniform Finish Blender   | SXA840 Uniform Finish Blender (Aerosol) | SU470LV 1K Compliant Adhesion Promoter          |
| SLV898 Retarder   | SXA1030 Black Guide Coat (Aerosol)      |   |

This AQMD Rule R307-354 (PPG Shop-Line) wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "AQMD Rule R307-354 (PPG Shop-Line)" wall chart does not include all currently compliant Shop-Line products. The representative products listed are compliant with AQMD Rule R307-354 VOC limits as of the date of this wall chart; however, subsequent changes in AQMD Rule R307-354 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.