



San Luis Obispo County APCD

Motor Vehicle and Mobile Equipment Coating Operations

Rule 423

Amended: 11/19/2008 | In Effect: 1/1/2010

ENVIROBASE®
HIGH PERFORMANCE

Coating Category		lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).			
Solvent (Surface Cleaner)*		0.21 (25)			
Product Code & Name		Hardener/Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)					
SWX350 H ₂ O-SO-CLEAN® Wax & Grease Remover		Limit: 0.21 lbs/gal (25 g/L)			
SX1009 2.9 VOC Bug & Tar Remover*		0.17 (20)			
SX1009 2.9 VOC Bug & Tar Remover*		2.89 (346)			
*Maximum 20 gal/yr/facility with a maximum VOC content of 6.5 lbs/gal allowed with recordkeeping requirements using non-aerosol handheld bottle.					
Product Code & Name		Hardener/Activator	Reducer	Additives	Mix Ratio
Pre-Treatment Coatings		Limit: 5.5 lbs/gal (660 g/L)			
SX1071 ECOBASE® 5.5 Etch Prime		SX1072	-	-	1:1
SXA1031 Etch Primer - Gray		-	-	-	Aerosol
SXA1031 Etch Primer - Gray		N/A			
Primer Surfacer		Limit 2.1 lbs/gal (250 g/L)			
ECP35 High Production Surfacer		EH391, EH392	ECRXX	-	4:1:1
ECP35 High Production Surfacer		EH391, EH392	ECRXX	SLV814	4:1:1:110%
DPLV Low VOC Epoxy Primer		DP401LV	DT18XX		2:1:1
EPW115 Waterborne Speed Prim		-	T494	-	1: 13%
EPW115 Waterborne Speed Prim		NCX455	DT18Xx		4:1:1
EPW115 Waterborne Speed Prim		0.72 (86)			
Primer Sealer (apply over previously coated surfaces)		Limit: 2.1 lbs/gal (250 g/L)			
ECS2X A-Chromatic LV Sealer		EH391, EH392	DT1845, DT1850, DT1855	-	4:1:1
ECS8X A-Chromatic LV Sealer		EH391, EH392	ECRXX, DT18XX	-	4:1:1
ECS8X A-Chromatic LV Sealer		2.05 (246)			
Basecoat for Multi Stage Topcoat System		Limit: 3.5 lbs/gal (420 g/L)			
Envirobase High Performance Basecoat		-	T494	-	100:10
Envirobase High Performance Basecoat		-	T494	-	100:20
Envirobase High Performance Basecoat		-	T494	-	100:30
Envirobase High Performance Basecoat		-	-	T492	100:10
Envirobase High Performance Basecoat		-	T494	T492	100:10:10
Envirobase High Performance Basecoat		-	T494	T492	100:20:10
Envirobase High Performance Basecoat		-	T494	T492	100:30:10
Envirobase High Performance Basecoat		T493	T494	T492	100:5:10:10
Envirobase High Performance Basecoat		T493	T494	T492	100:5:20:10
Envirobase High Performance Basecoat		T493	T494	T492	100:5:30:10
Envirobase High Performance Basecoat		T493	-	T492	100:5:10
Envirobase High Performance Basecoat		T4900	-	-	100:20
Envirobase High Performance Basecoat		T4900	T595	-	100:5:15
Envirobase High Performance Basecoat		T4910	T595	-	100:20
Envirobase High Performance Basecoat		T4910	T595	-	3.1 (371)
Envirobase High Performance Basecoat		3.27 (392)			
Envirobase High Performance Basecoat		3.1 (371)			
Envirobase High Performance Basecoat		3.3 (395)			
Envirobase High Performance Basecoat		3.1 (371)			



San Luis Obispo County APCD
 Motor Vehicle and Mobile Equipment Coating Operations
Rule 423
 Amended: 11/19/2008 | **In Effect: 1/1/2010**

ENVIROBASE®
HIGH PERFORMANCE

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Underbody Coatings (Specialty)					Limit: 3.6 lbs/gal (430 g/L)
Internal Repair System	T581	T494	-	100:15:15	3.08 (369)
Internal Repair System	T581	T494	-	100:15:20	3.09 (370)
Clearcoat for Multi Stage Topcoat System					Limit: 2.1 lbs/gal (250 g/L)
DC4125 Ceramiclear	DCH4126	-	-	2:1	2.05 (246)
EC520 En-V® High Production Clearcoat	ECH5075	ECRXX	-	3:1:1	2.07 (248)
EC530 En-V Performance Clearcoat	ECH5075	ECRXX	-	3:1:1	1.94 (232)
EC550 En-V Ultra Gloss Clearcoat	ECH5075	ECRXX	-	3:1:1	2.01 (241)
EC800 Ultra Fast 2.1 Clearcoat	ECH8075 ECH8075	DT1855 ECA83	-	4:1:1 4:1:1	2.08 (249) 1.90 (228)
EC5515 Low VOC Matte Clear	ECH5075	ECRXX, DT1855	-	3:1:1	2.02 (242)
EC5517 Low VOC Semi-Gloss Clear	ECH5075	ECRXX, DT1855		3:1:1	2.02 (242)
VC5250 DITZLER® Satin Clear	VH7250	DT18XX	-	4:1:1.5	1.86 (2.23)
VC5700 Ditzler Custom Clear	VH7780, VH7795	DT1855	-	2:1:1	2.08 (249)

Additional Products (listing not intended to be all inclusive)

SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacer (Aerosol)
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SX1047 High Build WB Flexible Surfacer
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)	SXA1041 Bumper Black (Aerosol)
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)	SU470LV 1K Compliant Adhesion Promoter

This "San Luis Obispo County APCD Rule 423 PPG Envirobase High Performance" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "San Luis Obispo County APCD Rule 423 PPG Envirobase High Performance" wall chart does not include all currently compliant PPG Envirobase High Performance products. The representative products listed are compliant with San Luis Obispo County APCD Rule 423 VOC limits as of the date of this wall chart; however, subsequent changes in San Luis Obispo County APCD Rule 423 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

The PPG logo, Envirobase, Ecobase, CeramiClear, En-V, Ditzler, One Visit and H₂O-So-Clean are trademarks of PPG Industries of Ohio, Inc.