South Coast AQMD—Phase 1

Motor Vehicle and Mobile Equipment Non-assembly Line Coating Operations

Rule 1151

Amended: 11/1/24 | **In Effect: 11/1/2024**

Coating Category	lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).
Solvent (Surface Cleaner)*	0.21 (25)
Pretreatment Coating	6.5 (780)
Primer / Primer Surfacer	4.8 (580)
Primer Sealer	4.6 (550)
Single Stage Coating	5.0 (600)
Color Coating	3.5 (420)
Tinted Mid-Coat	6.3 (750)
Underbody Coating	3.6 (430)
Clear Coating	4.3 (520)
Matte Clear Coating	4.6 (550)
Uniform Finish Coating	4.5 (540)
Adhesion Promoter	7.0 (840)

Product Code & Name	Hardener/ Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				**Limit: 0.21 lbs/gal (25 g/L)**
SWX350 H_2O-SO-CLEAN® Wax & Grease Remover	-	-	-	0.17 (20)

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings					**Limit: 6.5 lbs/gal (780 g/L)**
SXA1031 Etch Primer - Gray*	-	-	-	Aerosol	N/A
SX2071 Etch Primer - Gray	SX2072	-	-	2:1	2.05 (246)
**Products regulated as aerosol coatings and subject to applicable MIR limits under the California Aerosol Coating Product Regulation (Title 17, CCR, Sections 94520–94528)*					
Primer Surfacer					**Limit 4.8 lbs/gal (580 g/L)**
DPLF Epoxy Primer	DP401LF or DP402LF	-	-	2:1	4.6 (551)
DPLF Epoxy Primer	DP401LF or DP402LF	DT Series	-	2: 1: ¼	4.8 (575)
VP2x0 2K Urethane Primer Surfacer	VH330	VR25x	-	4: ½: 1	4.62 (554)
Primer Sealer (apply over previously coated surfaces)					**Limit: 4.6 lbs/gal (550 g/L)**
VS3x0 2K Urethane Primer Sealer	VH330	VR25x	-	4:1:2	4.35 (521)
Basecoat for Multi Stage Topcoat System					**Limit: 3.5 lbs/gal (420 g/L)**
QB Waterborne Basecoat	-	QR2960/QR2970	-	1:10%	0.77 (92)
QB Waterborne Basecoat	-	QR2960/QR2970	-	1:20%	0.72 (86)
QB Waterborne Basecoat	-	QR2960/QR2970	-	1:30%	0.68 (81)

© 2026 PPG Industries

South Coast AQMD– Phase 1

Motor Vehicle and Mobile Equipment Non-assembly Line Coating Operations

Rule 1151

Amended: 11/01/2024| **In Effect: 11/01/2024**

Clearcoat for Multi Stage Topcoat System					**Limit: 4.3 lbs/gal (520 g/L)**
VC200 HS Clear	VH20x	-	-	2:1	3.56 (427)
VC300 UHS Extra Clear	VH3x1	VR55x	-	2:1:½	3.66 (439)
VC400 UHS Rapid Clear	VH40x	-	-	2:1	3.66 (439)

Additional Products ***(listing not intended to be all inclusive)***		
SX840 Uniform Finish Blender	SU4903 Advanced Plastic Bond	SLV4985 Universal Flattening Agent
SXA840 Uniform Finish Blender (Aerosol)	SUA4903 Advanced Plastic Bond (Aerosol)	SL93LV Low VOC Accelerator
SU470LV 1K Adhesion Promoter (Aerosol)	SLV840 Uniform Finish Blender	OneChoice® Tack Rags
SU4901 Clean and Scuff Sponge	SU570 1K Adhesion Promoter	
SXA1050 Plastic Adhesion Promoter (Aerosol)	SLV814 Flexible Additive	

This “South Coast AQMD Rule 1151 PPG *Quickline/Velocity*” wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This “South Coast AQMD Rule 1151 PPG *Quickline/Velocity*” wall chart does not include all currently compliant PPG *Quickline*/Velocity products. The representative products listed are compliant with Rule 1151 VOC limits as of the date of this wall chart; however, subsequent changes in Rule 1151 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

The *PPG* logo, *Quickline, Multi-Prep, OneChoice, Velocity* and *H_2O-So-Clean* are trademarks of PPG Industries of Ohio, Inc.

© 2026 PPG Industries

Table 1- Table of Standards
Regulatory VOC Content Limits and Effective Dates for Automotive Coatings

Coating Categories	Current Limits[1]		Phase I Limits Effective November 1, 2024		Phase II Limits		
	g/L	lb/gal	g/L	lb/gal	g/L	lb/gal	Effective Date
Base Coatings							
Color Coating [2]	420	3.5			250	2.1	1/1/2030
Tinted Mid-Coat	420	3.5	750	6.3	250	2.1	1/1/2030
Clear Coatings							
Gloss Clear Coating	250	2.1	520	4.3	250	2.1	1/1/2030
Matte Clear Coating	250	2.1	550	4.6			
Primers and Sealers							
Pretreatment Wash Primer	660	5.5	780	6.5	660	5.5	1/1/2028
Epoxy Primer	250	2.1	580	4.8	340	2.8	1/1/2028
Primer Sealer	250	2.1	550	4.6	250	2.1	1/1/2029
Primer Surfacer	250	2.1	580	4.8	250	2.1	1/1/2029
Other Coating Categories							
Adhesion Promoter	540	4.5	840	7.0	720	6.0	1/1/2028
Single-Stage Coating	340	2.8	600	5.0	340	2.8	1/1/2028
Temporary Protective Coating	60	0.5					
Truck Bed Liner Coating	310	2.6					
Underbody Coating	430	3.6					
Uniform Finishing Coating	540	4.5					
Any Other Coating Type	250	2.1					

1 The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

2 See Paragraph (d)(4) for Color Coatings supplied in half-pint or smaller containers.

Table 4: pCBtF and t-BAc Prohibition Timeline

Category	Prohibition Effective Date	Sell-through End Date	Use-through End Date
Color Coatings	November 1, 2025	November 1, 2026	January 1, 2028
All Other Coating Categories	May 1, 2025	May 1, 2026	July 1, 2027