



South Coast AQMD
Motor Vehicle and Mobile Equipment Non-Assembly Line Coating Operations
Rule 1151
In Effect: 11/01/2024 Phase 1: 11/01/2025



Coating Category	lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).
Solvent (Surface Cleaner)*	0.21 (25)
Pretreatment Coating	6.5 (780)
Primer / Primer Surfacer	4.8 (580)
Primer Sealer	4.6 (550)
Single Stage Coating	5.0 (600)
Color Coating	3.5 (420)
Underbody Coating	3.6 (430)
Clear Coating	4.3 (520)
Uniform Finish Coating	4.5 (540)
Adhesion Promoter	7.0 (540)

Product Code & Name	Hardener/ Activator	Reducer	Mix Ratio	VOC Content	
Solvent (Surface Cleaner)				Limit: 0.21 lbs/gal (25 g/L)	
SWX350 H ₂ O-SO-CLEAN® Wax & Grease Remover	-	-	-	0.19 (20)	
Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings					Limit: 6.5 lbs/gal (780 g/L)
SXA1031 Etch Primer - Gray**	-	-	-	Aerosol	N/A
SX2071 Etch Primer - Gray	SX2072	-	-	2:1	2.05 (246)
**Products regulated as aerosol coatings and subject to applicable MIR limits under the California Aerosol Coating Product Regulation (Title 17, CCR, Sections 94520–94528)					
Primer Surfacer					Limit 4.8 lbs/gal (580 g/L)
JP202 High Build Primer Surfacer	JH301, JH302	JR50x	-	4:1:1	4.66 (558)
JP37X (Epoxy)	JH3770	-	-	2:1	4.54 (539)
Primer Sealer (apply over previously coated surfaces)					Limit: 4.6 lbs/gal (550 g/L)
JP43X Urethane Sealer	JH30X	JR50x		4:1:1	4.60 (550)
JP37X (Epoxy)	JH3770	Acetone		2:1: ½	4.54 (539)
Single Stage Coating					Limit: 5 lbs/gal (600 g/L)
JAU Direct Gloss Acrylic Urethane	JH66XX	JR55X	-	4:1:1	5.00 (599)
JE Acrylic Enamel	-	JR50X	-	4:1	5.00 (599)
JE Acrylic Enamel Activated	JH600X	JR50X	-	8:1:1	5.00 (599)
Basecoat for Multi Stage Topcoat System					Limit: 3.5 lbs/gal (420 g/L)
QB Quickline® Waterborne Basecoat	-	QR2960/QR2970		1:10%	0.77 (92)
QB Quickline Waterborne Basecoat	-	QR2960/QR2970	-	1:20%	0.72 (86)
QB Quickline Waterborne Basecoat	-	QR2960/QR2970	-	1:30%	0.68 (81)



South Coast AQMD
Motor Vehicle and Mobile Equipment Non-Assembly Line Coating Operations
Rule 1151
In Effect: 11/01/2024; Phase 1: 11/01/2025



Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Clear Coating					Limit: 4.3 lbs/gal (520 g/L)
JC630	JH63xx	-	-	4:1	4.18 (501)
JC6700	JH67xx	-	-	2:1	4.18 (500)
JC620	JH62xx	-	-	4:1	4.14 (496)

Additional Products (listing not intended to be all inclusive)		
SLV814 Universal Flexibilizer	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacers (Aerosol)
SL84 Enhancer Accelerator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1030 Black Guide Coat (Aerosol)
SL87 Extender	SWX100 Waterborne Gun Cleaner	SU570 AdPro
SX840 Uniform Finish Blender	SLV4985 Universal Flattening Agent	OneChoice® Tack Rags

This "South Coast AQMD Rule 1151 (PPG Shop-Line)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "South Coast AQMD Rule 1151 (PPG Shop-Line)" wall chart does not include all currently compliant Shop-Line products. The representative products listed are compliant with South Coast AQMD Rule 1151 VOC limits as of the date of this wall chart; however, subsequent changes in South Coast AQMD Rule 1151 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

Table 1- Table of Standards
Regulatory VOC Content Limits and Effective Dates for Automotive Coatings

Coating Categories	Current Limits ⁽¹⁾		Phase I Limits Effective November 1, 2024		Phase II Limits		
	g/L	lb/gal	g/L	lb/gal	g/L	lb/gal	Effective Date
Base Coatings							
Color Coating ⁽²⁾	420	3.5			250	2.1	1/1/2030
Tinted Mid-Coat	420	3.5	750	6.3	250	2.1	1/1/2030
Clear Coatings							
Gloss Clear Coating	250	2.1	520	4.3	250	2.1	1/1/2030
Matte Clear Coating	250	2.1	550	4.6			
Primers and Sealers							
Pretreatment Wash Primer	660	5.5	780	6.5	660	5.5	1/1/2028
Epoxy Primer	250	2.1	580	4.8	340	2.8	1/1/2028
Primer Sealer	250	2.1	550	4.6	250	2.1	1/1/2029
Primer Surfacer	250	2.1	580	4.8	250	2.1	1/1/2029
Other Coating Categories							
Adhesion Promoter	540	4.5	840	7.0	720	6.0	1/1/2028
Single-Stage Coating	340	2.8	600	5.0	340	2.8	1/1/2028
Temporary Protective Coating	60	0.5					
Truck Bed Liner Coating	310	2.6					
Underbody Coating	430	3.6					
Uniform Finishing Coating	540	4.5					
Any Other Coating Type	250	2.1					

1 The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

2 See Paragraph (d)(4) for Color Coatings supplied in half-pint or smaller containers.