



# San Diego County APCD

Motor Vehicle and Mobile Equipment Coating Operations

## Rule 67.20.1

Amended: 6/30/2010 | In Effect: 6/30/2010

**ENVIROBASE®**  
**HIGH PERFORMANCE**

| Coating Category           | lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts). |   |
|----------------------------|---|---|
| Solvent (Surface Cleaner)* | 0.21 (25)   |   |
| Pretreatment Coating       | 5.5 (660)   |   |
| Primer / Primer Surfacer   | 2.1 (250)   |   |
| Primer Sealer              | 2.1 (250)   |   |
| Single Stage Coating       | 2.8 (340)   |   |
| Color Coating              | 3.5 (420)   |   |
| Underbody Coating          | 3.6 (430)   |   |
| Clear Coating              | 2.1 (250)   |   |
| Uniform Finish Coating     | 4.5 (540)   |   |
| Adhesion Promoter          | 4.5 (540)   | *VOC content applies to this category only. |

| Product Code & Name                                    | Hardener/<br>Activator | Reducer | Mix Ratio | VOC Content                  |
|--|------------------------|---------|-----------|------------------------------|
| <b>Solvent (Surface Cleaner)</b>                       |                        |         |           | Limit: 0.21 lbs/gal (25 g/L) |
| SWX350 H <sub>2</sub> O-SO-CLEAN® Wax & Grease Remover | -                      | -       | -         | 0.17 (20)                    |
| SX330 ACRYLI-CLEAN® Wax and Grease Remover*            | -                      | -       | -         | 6.31 (756)                   |
| SX394 1.4 Low VOC Cleaner*                             | -                      | -       | -         | 1.34 (161)                   |
| SX1009 2.9 VOC Bug & Tar Remover*                      | -                      | -       | -         | 2.89 (346)                   |

\*67.20.1 (b) (6) allows cleaning material for dust, wax, grease, tar or bugs if less than 6.5 lbs/gal applied with non-aerosol, hand-held spray bottle, not more than 20 gal. per year (records of use should be kept)

| Product Code & Name  | Hardener/Activator | Reducer       | Additives | Mix Ratio  | Applied VOC<br>Less Water Less Exempt |
|--|--------------------|---------------|-----------|------------|---------------------------------------|
| <b>Pre-Treatment Coatings</b>                                |                    |               |           |            | Limit: 5.5 lbs/gal (660 g/L)          |
| SX1071 ECOBASE® 5.5 Etch Prime                               | SX1072             | -             | -         | 1:1        | 5.48 (657)                            |
| SXA1031 Etch Primer - Gray                                   | -                  | -             | -         | Aerosol    | N/A                                   |
| <b>Primer Surfacer</b>                                       |                    |               |           |            | Limit 2.1 lbs/gal (250 g/L)           |
| ECP35 High Production Surfacer                               | EH391, EH392       | ECRXX         | -         | 4:1:1      | 1.71 (205)                            |
| ECP35 High Production Surfacer                               | EH391, EH392       | ECRXX         | SLV814    | 4:1:1:110% | 1.67 (200)                            |
| DPLV 2.1 Low VOC Epoxy Primer                                | DP401LV            | DT18XX        |           | 2:1:1      | 1.16 (139)                            |
| EPW115 Waterborne Speed Prim                                 | -                  | T494          | -         | 1: 13%     | 0.72 (86)                             |
| NCP450 Iso-Free Primer                                       | NCX455             | DT18XX        | -         | 4:1:1      | 1.33 (174)                            |
| <b>Primer Sealer (apply over previously coated surfaces)</b> |                    |               |           |            | Limit: 2.1 lbs/gal (250 g/L)          |
| ECS2X A-Chromatic LV Sealer                                  | EH391, EH392       | DT18XX        | -         | 4:1:1      | 2.05 (246)                            |
| ECS8X A-Chromatic LV Sealer                                  | EH391, EH392       | ECRXX, DT18XX | -         | 4:1:1      | 2.07 (248)                            |



# San Diego County APCD

Motor Vehicle and Mobile Equipment Coating Operations

## Rule 67.20.1

Amended: 6/30/2010 | In Effect: 6/30/2010

**ENVIROBASE®**  
**HIGH PERFORMANCE**

| Product Code & Name   | Hardener/Modifier/Activator             | Reducer         | Additives                                      | Mix Ratio      | Applied VOC<br>Less Water Less Exempt |
|---|---|-----------------|--|----------------|---------------------------------------|
| <b>Basecoat for Multi Stage Topcoat System</b>                        |   |                 |  |                | Limit: 3.5 lbs/gal (420 g/L)          |
| Envirobase High Performance Basecoat                                  | -                                       | T494            | -  | 100:10         | 3.33 (399)                            |
| Envirobase High Performance Basecoat                                  | -                                       | T494            | -  | 100:20         | 3.38 (405)                            |
| Envirobase High Performance Basecoat                                  | -                                       | T494            | -  | 100:30         | 3.50 (420)                            |
| Envirobase High Performance Basecoat                                  | -                                       | -               | T492   | 100:10         | 2.78 (333)                            |
| Envirobase High Performance Basecoat                                  | -                                       | T494            | T492   | 100:10:10      | 3.24 (388)                            |
| Envirobase High Performance Basecoat                                  | -                                       | T494            | T492   | 100:20:10      | 3.28 (393)                            |
| Envirobase High Performance Basecoat                                  | -                                       | T494            | T492   | 100:30:10      | 3.28 (393)                            |
| Envirobase High Performance Basecoat                                  | T493                                    | T494            | T492   | 100:5:10:10    | 3.21 (385)                            |
| Envirobase High Performance Basecoat                                  | T493                                    | T494            | T492   | 100:5:20:10    | 3.24 (388)                            |
| Envirobase High Performance Basecoat                                  | T493                                    | T494            | T492   | 100:5:30:10    | 3.25 (389)                            |
| Envirobase High Performance Basecoat                                  | T493                                    | -               | T492   | 100:5:10       | 2.81 (337)                            |
| Envirobase High Performance Basecoat                                  | T4900                                   | -               | -  | 100:20         | 3.27 (392)                            |
| Envirobase High Performance Basecoat                                  | T4900                                   | T595            | -  | 100:5:15       | 3.1 (371)                             |
| Envirobase High Performance Basecoat                                  | T4910                                   | T595            | -  | 100:20         | 3.3 (395)                             |
| Envirobase High Performance Basecoat                                  | T4910                                   | T595            | -  | 100:5:15       | 3.1 (371)                             |
| <b>Underbody Coatings (Specialty)</b>                                 |   |                 |  |                | Limit: 3.6 lbs/gal (430 g/L)          |
| Internal Repair System  | T581                                    | T494            | -  | 100:15:15      | 3.08 (369)                            |
| Internal Repair System  | T581                                    | T494            | -  | 100:15:20      | 3.09 (370)                            |
| <b>Clearcoat for Multi Stage Topcoat System</b>                       |   |                 |  |                | Limit: 2.1 lbs/gal (250 g/L)          |
| DC4125 Ceramiclear  | DCH4126                                 |                 |  | 2:1            | 2.05 (246)                            |
| EC520 En-V® High Production Clearcoat                                 | ECH5075                                 | ECRXX           |  | 3:1:1          | 2.07 (248)                            |
| EC530 En-V Performance Clearcoat                                      | ECH5075                                 | ECRXX           |  | 3:1:1          | 1.94 (232)                            |
| EC550 En-V Ultra Gloss Clearcoat                                      | ECH5075                                 | ECRXX           |  | 3:1:1          | 2.01 (241)                            |
| EC800 Ultra Fast 2.1 Clearcoat  | ECH8075<br>ECH8075                      | DT1855<br>ECA83 |  | 4:1:1<br>4:1:1 | 2.08 (249)<br>1.90 (228)              |
| EC5515 Low VOC Matte Clear  | ECH5075                                 | ECRXX, DT1855   |  | 3:1:1          | 2.02 (242)                            |
| EC5517 Low VOC Semi-Gloss Clear                                       | ECH5075                                 | ECRXX, DT1855   |  | 3:1:1          | 2.02 (242)                            |
| VC5250 DITZLER® Satin Clear   | VH7250                                  | DT18XX          | -  | 4:1:1.5        | 1.86 (2.23)                           |
| VC5700 Ditzler Custom Clear   | VH7780, VH7795                          | DT1855          | -  | 2:1:1          | 2.08 (249)                            |
| <b>Additional Products (listing not intended to be all inclusive)</b> |   |                 |  |                |                                       |
| SLV4985 Universal Flattening Agent                                    | SU4901 Clean and Scuff Sponge           |                 | SXA1044 High Build Flexible Surfacer (Aerosol) |                |                                       |
| SLV73 Fisheye Eliminator  | SUA4903 Advanced Plastic Bond (Aerosol) |                 | SXA1050 Plastic Adhesion Promoter (Aerosol)    |                |                                       |
| SLV814 Universal Flexibilizer   | SWX100 Waterborne Gun Cleaner           |                 | SU470LV 1K Compliant Adhesion Promoter         |                |                                       |
| SLV840 Uniform Finish Blender   | SXA840 Uniform Finish Blender (Aerosol) |                 |  |                |                                       |
| SLV898 Retarder   | SXA1030 Black Guide Coat (Aerosol)      |                 |  |                |                                       |

This "San Diego County APCD Rule 67.20.1 PPG Envirobase High Performance" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "San Diego County APCD Rule 67.20.1 PPG Envirobase High Performance" wall chart does not include all currently compliant PPG Envirobase High Performance products. The representative products listed are compliant with San Diego County APCD Rule 67.20.1 VOC limits as of the date of this wall chart; however, subsequent changes in San Diego County APCD Rule 67.20.1 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

The PPG logo, Envirobase, Acryli-Clean, Multi-Prep, Ecobase, CeramiClear, En-V, Ditzler, One Visit and H<sub>2</sub>O-So-Clean are trademarks of PPG Industries of Ohio, Inc.