Utah R307-354

Automotive Refinish Coatings

Applies to Box Elder, Cache, Davis, Salt Lake, Tooele, Utah and Weber counties. Before September 1, 2018, applies to operations that have the potential to emit (PTE) 2.7 tons/year or more of VOC, including related cleaning activities. Effective September 1, 2018, R307-354 shall apply to an automotive refinishing operation that uses a combined 20 gallons or more of coating products and associated solvents/year.

Amended: 12/6/2017 | **In Effect: 9/1/2018**

Coating Category	lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).
Pretreatment Coating	5.5 (660)
Primer / Primer Surfacer	2.1 (250)
Primer Sealer	2.1 (250)
Single Stage Coating	2.8 (340)
Color Coating	3.5 (420)
Underbody Coating	3.6 (430)
Clear Coating	2.1 (250)
Uniform Finish Coating	4.5 (540)
Adhesion Promoter	4.5 (540)

Product Code & Name	Hardener/ Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				**Limit: n/a**
SWX350 H_2O-SO-CLEAN® Wax & Grease Remover	-	-	-	0.17 (20)
SX1009 2.9 VOC Bug and Tar Remover	-	-	-	6.36 (762)
SX103 MULTI-PREP®	-	-	-	6.49 (778)
SX330 Wax and Grease Remover	-	-	-	6.36 (762)
SX394 1.4 Low VOC Cleaner	-	-	-	1.34 (161)

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings					**Limit: 5.5 lbs/gal (660 g/L)**
SX2071 Etch Primer	SX2072			2:1	2.05 (246)
SXA1031 Etch Primer - Gray*	-	-	-	Aerosol	N/A
**Product regulated as aerosol coatings and subject to applicable PWR/MIR limits under EPA 40 CFR Part 59.*					
Primer Surfacer					**Limit 2.1 lbs/gal (250 g/L)**
QP-5x00 Low VOC Primer Surfacer	QH-3800	QR-29xx	-	4:1:2	1.0 (120)
QP-5x00 Low VOC Primer Surfacer	QH-3800	QR-29xx	SLV814	4:1:2:10%	0.94 (113)
DPLV Low VOC Epoxy Primer	DP401LV	DT18XX		2:1:1	1.16 (139)
Primer Sealer (apply over previously coated surfaces)					**Limit: 2.1 lbs/gal (250 g/L)**
QS-3x00 Low VOC Primer Sealer	QH-3800	QR-29xx	-	4:1:1	1.15 (138)
QS-3x00 Low VOC Primer Sealer	QH-3800	QR-29xx	SLV814	4:1:1:10%	1.08 (129)
Basecoat for Multi Stage Topcoat System					**Limit: 3.5 lbs/gal (420 g/L)**
QB Waterborne Basecoat	-	QR2960/QR2970	-	1:10%	0.77 (92)
QB Waterborne Basecoat	-	QR2960/QR2970	-	1:20%	0.72 (86)
QB Waterborne Basecoat	-	QR2960/QR2970	-	1:30%	0.68 (81)
Clearcoat for Multi Stage Topcoat System					**Limit [1, 2]: 5.0 / 5.2 lbs/gal (600 / 624 g/L)**
QC-4000 Low VOC Glamour Clear	QH-4x00	QR-29xx	-	3:1: ½	1.11 (132)
QC-9000 Low VOC Speed Clear	QH-9x00	-	-	4:1	1.08 (129)
QC-9000 Low VOC Speed Clear	QH-9x00	-	SL93LV	4:1:2%	1.06 (127)
QC-9000 Low VOC Speed Clear	QH-9x00	-	SLV814	3:1:½	0.97 (116)

© 2026 PPG Industries

Utah R307-354

Automotive Refinish Coatings

Applies to Box Elder, Cache, Davis, Salt Lake, Tooele, Utah and Weber counties. Before September 1, 2018, applies to operations that have the potential to emit (PTE) 2.7 tons/year or more of VOC, including related cleaning activities. Effective September 1, 2018, R307-354 shall apply to an automotive refinishing operation that uses a combined 20 gallons or more of coating products and associated solvents/year.

Amended: 12/6/2017 | **In Effect: 9/1/2018**

Additional Products ***(listing not intended to be all inclusive)***		
SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacer (Aerosol)
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SU470LV 1K Compliant Adhesion Promoter
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)	
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)	

This “Utah R307-354 Automotive Refinish Coatings PPG Quickline” wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This “Utah R307-354 Automotive Refinish Coatings PPG Quickline” wall chart does not include all currently compliant PPG Quickline products. The representative products listed are compliant with Utah R307-354 VOC limits as of the date of this wall chart; however, subsequent changes in Utah R307-354 may change the compliance status of the listed products. It is the responsibility of the end user to Utah R307-354 review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

The *PPG* logo, *Quickline* and *H_2O-So-Clean* are trademarks of PPG Industries of Ohio, Inc.