



Matthews Paint Finish Maintenance

The maintenance and care of a painted or clearcoated Matthews polyurethane surface should utilize commercially available non-abrasive cleaners and polishes/waxes recommended for finishes exposed to the environment.


For new finishes, it is recommended to wait at least 30 days after painting before any cleaning, polishing or waxing* is attempted to allow the finish to fully cure.

Fully cured finishes should be routinely cleaned to remove dirt, hard water spots/staining, or other forms of environmental or biological contamination.

***Caution:** Although polishes or waxes can be used to clean and protect gloss finishes, their use over low-gloss finishes may result in an increased gloss level.

General Maintenance Guidelines:

- Remove animal droppings or tree sap upon discovery, as they can do permanent damage to the finish.
- Use mild detergent water solution utilizing a soft wash mitt or cloth followed by a thorough clean water rinse.
- Dry with a damp chamois, microfiber towel, or soft cloth.
- **Full gloss finishes:** if polishing or waxing is desired, apply with a soft, damp, cloth-covered sponge and buff with a soft microfiber cloth. Procedure best performed in the cooler hours of the day, avoiding direct sunlight if possible.
- **Low-gloss finishes:** polishing or waxing is generally **NOT recommended**. If polishing or waxing is desired, be sure to use a product specifically designed for low-gloss finishes and follow all manufacturer's recommendations. Always test the product in an **inconspicuous** area before using on the entire surface.



Precautions:

- Do not wash*, polish or wax a finish that is less than 30 days old.
- Do not use abrasive detergents or harsh chemicals to clean surface.
- Exposure to water sprinklers on the painted surface can cause hard water stains.
- Use caution when cleaning painted surfaces with a pressure washer. **DO NOT** use pressure washers that exceed 1,200 psi.
- Do not use a mechanical polisher or buffer on low-gloss finishes.
- For low-gloss finishes, do not use any type of wax, polish, or any other product made for full gloss finishes.
- Once a low-gloss finish has become damaged or glossy, the original low-gloss appearance cannot be restored without refinishing.
- Do not use chemical cleaners on acrylic or polycarbonate.

*If necessary, gently wash a new finish with clean water and a soft wash mitt and dry immediately.

If you have any questions, call Matthews Paint toll-free 1-800-323-6593.

Important: Use appropriate Personal Protective Equipment (PPE) and observe all applicable precautions

See Safety Data Sheet and Labels for additional safety information and handling instructions.

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION - US (412) 434-4515; CANADA (514) 645-1320; Mexico 01-800-00-21-400
Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.



The World's Finest Coating For Architectural Signage

760 Pittsburgh Drive
Delaware, OH 43015
Toll Free: 800/323-6593
Toll Free FAX: 800/947-0377