PREDICTED ENERGY ASSESSMENT



Plot 161, 2 Bed, 1B, 0ES, Honiton, Devon Dwelling type: Flat, End-Terrace

Date of assessment: 05/03/2021


Produced by: Mitchell Bennellick

Total floor area: 57.41 m²

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.


The energy performance has been assessed using the Government approved SAP2012 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO₂) emissions.

Energy Efficiency Rating



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

Environmental Impact (CO₂) Rating



The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO₂) emissions. The higher the rating the less impact it has on the environment.

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



Property Reference 4907-0023-3730)-161			Issued on Date	05/03/2021	
Assessment Plot 161		Pro	op Type Ref	Block F - 2F Apartme	ent	
Reference						
Property Plot 161, 2 Bed,	1B, 0ES, Honiton, Devon					
SAP Rating	83 B	DER	18.39	TER	19.66	
Environmental	87 B	% DER <ter< td=""><td></td><td>6.44</td><td></td></ter<>		6.44		
CO ₂ Emissions (t/year)	0.89	DFEE	44.60	TFEE	49.39	
General Requirements Compliance	Pass	% DFEE <tfee< td=""><td></td><td>9.71</td><td></td></tfee<>		9.71		
-	Lindsey Dean, Tel: 01884	242050,		Assessor ID	P635-0001	
Lindsey.dean@aess	c.co.uk					
Client Baker Estates						
SUMARY FOR INPUT DATA FOR New Buil	ld (As Designed)					
Criterion 1 – Achieving the TER and TFEE	rate					
1a TER and DER						
Fuel for main heating	Mains gas					
Fuel factor	1.00 (main	ns gas)				
Target Carbon Dioxide Emission Rate	(TER) 19.66			kgCO ₂ /m ²		
Dwelling Carbon Dioxide Emission Rat	te (DER) 18.39			kgCO₂/m²	Pass	
4h TEEE and DEEE	-1.27 (-6.5	5%)		kgCO ₂ /m ²		
1b TFEE and DFEE	40.00			100/1/27		
Target Fabric Energy Efficiency (TFEE)		49.39 kWh/m²/y				
Dwelling Fabric Energy Efficiency (DFE	44.60 -4.8 (-9.79	V/)		kWh/m²/yr		
Criterion 2 – Limits on design flexibility	-4.8 (-9.77	(6)		KVVII/III / yI	Pass	
Limiting Fabric Standards						
2 Fabric U-values						
Element	Average	11:	ahaat			
External wall	Average 0.22 (max. 0.30)		ghest 32 (max. 0.70	١	Pass	
Party wall	0.22 (max. 0.30)	0.:	52 (IIIdx. U.70)	Pass	
Roof	0.13 (max. 0.20)	0.7	24 (max. 0.35)	Pass	
Openings	1.33 (max. 2.00)					
2a Thermal bridging	2.00 (1.0	(5.50	,	Pass	
	linear thermal transmitta	inces for each iun	nction			
Thermal bridging calculated from 1						
Thermal bridging calculated from I						
3 Air permeability		gn value)		m³/(h m²\	a	
3 Air permeability Air permeability at 50 pascals	5.00 (desi	gn value)		m ³ /(h.m ²) @ 50 P m ³ /(h.m ²) @ 50 P		
3 Air permeability		gn value)		m ³ /(h.m ²) @ 50 P m ³ /(h.m ²) @ 50 P		

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



Regs Region: England Elmhurst Energy Systems SAP2012 Calculator (Design System) version 4.14r16

BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



Main heating system	Boiler system with radiators or underfloor - Mains gas	Pass			
	Data from database				
	Ideal LOGIC COMBI ESP1 35				
	Combi boiler				
	Efficiency: 89.6% SEDBUK2009				
	Minimum: 88.0%				
Secondary heating system	None				
5 Cylinder insulation					
Hot water storage	No cylinder				
<u>6 Controls</u>					
Space heating controls	Time and temperature zone control	Pass			
Hot water controls	No cylinder				
Boiler interlock	Yes	Pass			
7 Low energy lights					
Percentage of fixed lights with low-energy	100 %				
fittings					
Minimum	75 %	Pass			
8 Mechanical ventilation					
Not applicable					
Criterion 3 – Limiting the effects of heat gains in sur	nmer				
9 Summertime temperature					
Overheating risk (South West England)	Not significant	Pass			
Based on:					
Overshading	Average				
Windows facing South East	3.26 m², No overhang				
Windows facing North West	2.03 m ² , No overhang				
Air change rate	6.00 ach				
Blinds/curtains	None				
Criterion 4 – Building performance consistent with	DER and DFEE rate				
Party Walls					
Туре	U-value				
Filled Cavity with Edge Sealing	0.00 W/m ² K	Pass			
Air permeability and pressure testing					
3 Air permeability					
Air permeability at 50 pascals	5.00 (design value) m ³ /(h.m ²) @ 50 Pa				
Maximum	10.0 m ³ /(h.m ²) @ 50 Pa	Pass			
10 Key features					
Party wall U-value	0.00 W/m ² K				
Roof U-value	0.11 W/m²K				
Roof U-value	0.11 W/m²K				
Door U-value	0.83 W/m²K				
5501 6 value	w/III K				

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.




Regs Region: England Elmhurst Energy Systems SAP2012 Calculator (Design System) version 4.14r16

RECOMMENDATIONS



	Typical cost	Typical savings per year	Energy efficiency	Environmental impact	Result
Low energy lights			0	0	Already installed
Solar water heating			0	0	Not applicable
Photovoltaic			0	0	Not applicable
Wind turbine			0	0	Not applicable
Totals	fO	fO	B 83	B 87	



This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



Regs Region: England Elmhurst Energy Systems SAP2012 Calculator (Design System) version 4.14r16