



South Coast AQMD
 Motor Vehicle and Mobile Equipment Nonassembly Line Coating Operations
Rule 1151
 Amended: 12/2/2005 | In Effect: 1/1/2010



Coating Category	lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).
Solvent (Surface Cleaner)*	0.21 (25)
Pretreatment Coating	5.5 (660)
Primer / Primer Surfacer	2.1 (250)
Primer Sealer	2.1 (250)
Single Stage Coating	2.8 (340)
Color Coating	3.5 (420)
Underbody Coating	3.6 (430)
Clear Coating	2.1 (250)
Uniform Finish Coating	4.5 (540)
Adhesion Promoter	4.5 (540)

*VOC content applies to this category only.

Product Code & Name	Hardener/Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				Limit: 0.21 lbs/gal (25 g/L)
SWX350 H ₂ O-SO-CLEAN [®] Wax & Grease Remover	-	-	-	0.17 (20)
SXA103 MULTI-PREP [™] Cleaner	-	-	Aerosol	5.88 (705)
SXA330 Wax & Grease Remover	-	-	Aerosol	5.77 (691)

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings					Limit: 5.5 lbs/gal (660 g/L)
SX1071 ECOBASE [®] 5.5 Etch Prime	SX1072	-	-	1:1	5.48 (657)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer Surfacer					Limit 2.1 lbs/gal (250 g/L)
P565-540X HS Plus Primer Surfacer	P210-5475	P850-1775	-	4:1	2.08 (249)
P565-540X HS Plus Primer Surfacer	P210-5475	P850-1775	-	4:1:1	2.08 (249)
P565-540X HS Plus Primer Surfacer	P210-5475	P850-1775	SL93LV	4:1:1 + 10%	2.08 (249)
P950-5505 Waterborne Primer Surfacer	-	P980-5000	-	1:13%	0.72 (86)
DPLV 2.1 Epoxy Primer	DP401LV	D8764, D8774, D8767	-	2:1:1	2.09 (250)
Primer Sealer (apply over previously coated surfaces)					Limit: 2.1 lbs/gal (250 g/L)
P565-314X HS Plus Wet-On-Wet Sealer LV	P210-5475	P850-1775	-	4:1:1	1.82 (218)
Single Stage Coating					Limit: 2.8 lbs/gal (340 g/L)
P989 AQUABASE [®] Plus Interior System	P210-9136	P980-5000	-	100:15:15	2.79 (334)
Basecoat for Multi Stage Topcoat System					Limit: 3.5 lbs/gal (420 g/L)
P989 Aquabase Plus Basecoat	-	P980-5000	-	100:10	3.33 (399)
P989 Aquabase Plus Basecoat	-	P980-5000	-	100:20	3.38 (405)
P989 Aquabase Plus Basecoat	-	P980-5000	-	100:30	3.50 (419)
P989 Aquabase Plus Basecoat	-	-	P935-1250	100:10	2.78 (333)
P989 Aquabase Plus Basecoat	-	P980-5000	P935-1250	100:10:10	3.24 (388)
P989 Aquabase Plus Basecoat	-	P980-5000	P935-1250	100:20:10	3.28 (393)
P989 Aquabase Plus Basecoat	-	P980-5000	P935-1250	100:30:10	3.28 (393)
P989 Aquabase Plus Basecoat	P935-1255	P980-5000	P935-1250	100:5:10:10	3.21 (385)
P989 Aquabase Plus Basecoat	P935-1255	P980-5000	P935-1250	100:5:20:10	3.24 (388)



South Coast AQMD
 Motor Vehicle and Mobile Equipment Nonassembly Line Coating Operations
Rule 1151
 Amended: 12/2/2005 | In Effect: 1/1/2010



Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Basecoat for Multi Stage Topcoat System					Limit: 3.5 lbs/gal (420 g/L)
P989 Aquabase Plus Basecoat	P935-1255	P980-5000	P935-1250	100:5:30:10	3.25 (389)
P989 Aquabase Plus Basecoat	P935-1255	-	P935-1250	100:5:10	2.81 (337)
Underbody Coatings (Specialty)					Limit: 3.6 lbs/gal (430 g/L)
P989 Aquabase Plus Engine Bay Color	P210-9120	P980-5000	-	100:15:15	3.08 (369)
P989 Aquabase Plus Engine Bay Color	P210-9120	P980-5000	-	100:15:20	3.09 (370)
Clear Coating					Limit: 2.1 lbs/gal (250 g/L)
P190-6490 Scratch Resistant Clearcoat	P210-8490	-	-	2:1	2.00 (240)
P190-6730 HS Plus Clearcoat	P210-65XX	P850-1775	-	3:1:10%	2.05 (246)
P190-6759 Express Clearcoat LV	P210-87X	P850-1775	-	3:1:1.5	2.08 (249)
P190-6759 Express Clearcoat LV	P210-87X	P850-1775	SL93LV	3:1:1:2%	2.08 (249)
P190-6759 Express Clearcoat LV	P210-87X	P850-1775	SL93LV	3:1:1.5:2%	2.08 (249)
P190-6759 Express Clearcoat LV	P210-87X	P850-1775	-	3:1:1	2.08 (249)
P190-6790 HS Clearcoat LV	P210-87X	P850-1775	-	3:1:1	2.08 (249)
P190-6790 HS Clearcoat LV	P210-87X	P850-1775	-	3:1:1.5	2.08 (249)
P190-6800 HS Express Clearcoat	P210-6875 P210-6875	P850-1775 P852-1683	-	4:1:1 4:1:1	1.90 (228) 2.08 (249)
P190-6920 Production Clearcoat	P210-6975	P850-691X	-	3:1:1	2.07 (248)
P190-6930 Performance Clearcoat	P210-6975	P850-691X	-	3:1:1	1.94 (232)
P190-6950 Extended Performance Clearcoat	P210-6975	P850-691X	-	3:1:1	2.01 (241)
P910-5510 Waterborne Clearcoat	P210-8860	P980-5000	-	5:2:2	2.09 (250)

Additional Products (listing not intended to be all inclusive)		
P100-2021 Flexible Additive	SLV898 Retarder	SXA1044 High Build Flexible Surfacer
SLV4985 Universal Flattening Agent	SU470LV 1K Compliant Adhesion Promoter	SXA1050 Plastic Adhesion Promoter
SLV73 Fisheye Eliminator	SU4901 Clean and Scuff Sponge	SX1047 High Build WB Flexible Surfacer
SLV814 Universal Flexibilizer	SUA4903 Advanced Plastic Bond (Aerosol)	SWX100 Waterborne Gun Cleaner
SLV840 Uniform Finish Blender	SXA1030 Black Guide Coat (Aerosol)	
SXA840 Uniform Finish Blender	SXA1041 Bumper Black (Aerosol)	

This "South Coast AQMD Rule 1151 PPG Nexa Autocolor" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "South Coast AQMD Rule 1151 PPG Nexa Autocolor" wall chart does not include all currently compliant PPG Nexa Autocolor products. The representative products listed are compliant with Rule 1151 VOC limits as of the date of this wall chart; however, subsequent changes in Rule 1151 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

Nexa Autocolor, Aquabase, Multi-Prep, Ecobase, and H₂O-So-Clean are trademarks of PPG Industries of Ohio, Inc.