



Yolo-Solano AQMD
 Motor Vehicle and Mobile Equipment Coating Operations
Rule 2.26
 Amended: 12/10/2008 | In Effect: 7/1/2010



Coating Category*	lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).
Solvent (Surface Cleaner)*	0.21 (25)
Pretreatment Coating	5.5 (660)
Primer / Primer Surfacer	2.1 (250)
Primer Sealer	2.1 (250)
Single Stage Coating	2.8 (340)
Color Coating	3.5 (420)
Underbody Coating	3.6 (430)
Clear Coating	2.1 (250)
Uniform Finish Coating	4.5 (540)
Adhesion Promoter	4.5 (540)

*VOC content applies to this category only

Product Code & Name	Hardener/Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				Limit: 0.21 lbs/gal (25 g/L)
SWX350 H ₂ O-SO-CLEAN [®] Wax and Grease Remover	-	-	-	0.17 (20)
SXA103 MULTI-PREP [™] Cleaner*	-	-	Aerosol	5.88 (705)
SXA330 Wax and Grease Remover*	-	-	Aerosol	5.77 (691)

* Rule 2.31 section 113 limited exemption for cleaning with aerosol products up to 160 fluid ounces per day per facility and facility has a District permit or written exemption from the APCO.

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings					Limit: 5.5 lbs/gal (660 g/L)
SX1071 ECOBASE [®] 5.5 Etch Prime	SX1072	-	-	1:1	5.48 (657)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer / Primer Surfacer					Limit 2.1 lbs/gal (250 g/L)
MP80x 2.1 VOC Multi-Purpose Primer	MH810	MR29x	-	4:1:2	1.96 (236)
MP871 2.1 VOC Epoxy Primer	MP875	MR29x	-	2:1:1	2.07 (248)
MP243 Polyester Primer	MEKP (MX199)	-	-	1 tube/qt	1.64 (196)
Primer Sealer (apply over previously coated surfaces)					Limit: 2.1 lbs/gal (250 g/L)
MP80X Multi-Purpose Primer	MH810	MR29X	MC262 or MC770	3:1:1:1	2.02 (242)
MP871 2.1 VOC Epoxy Primer	MP875	MR29X	-	2:2:1	2.07 (248)
MP89x 2.1 VOC Urethane Sealers	MH810	MR29x	-	4:1:1	2.01 (241)
Single Stage Coating					Limit: 2.8 lbs/gal (340 g/L)
MLX 2.8 VOC Acrylic Enamel	MH238	MR29x	-	4:1:1	2.76 (331)
MTX 2.8 VOC Single Stage	MH238	MR29x	-	4:1:2	2.80 (336)
Basecoat for Multi Stage Topcoat System					Limit: 3.5 lbs/gal (420 g/L)
MBX OMNI [®] 3.5 VOC Acrylic Basecoat	-	MR29x	-	1:1	3.5 (419)
Use MBPX blend to spray mix recommendation without MH238 only with color formulas that contain M799					
MBPX <i>Omni</i> Plus 3.5 Basecoat	-	MR29x	-	1:1	3.48 (417)
Use MBPX blend to spray mix recommendations with MH238 with all historic color formulas that contain M736					
MBPX <i>Omni</i> Plus 3.5 Basecoat	MH238	MR29x	-	10:1:10	3.48 (417)
MBPX <i>Omni</i> Plus 3.5 Basecoat	MH238	MR29x	-	10:1:5	3.48 (417)



Yolo-Solano AQMD
 Motor Vehicle and Mobile Equipment Coating Operations
Rule 2.26



Amended: 12/10/2008 | In Effect: 7/1/2010

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Clear Coating					Limit: 2.1 lbs/gal (250 g/L)
MC262 <i>Omni</i> 2.1 VOC 4+1 Urethane Clear	MH266, MH267	-	-	4:1	2.08 (249)
MC730 2.1 VOC Production Clear	MH737, MH738, MH739	MR295, MR296	-	4:1:0.5	2.08 (249)
MC760 2.1 VOC Universal Clear	MH267, MH268	MR295, MR296	-	4:1:1	2.08 (249)
MC2910 2.1 VOC EUROPLUS® Multi-Panel Clearcoat	MH2918, MH2919	-	-	2:1	1.95 (234)
MC2980 2.1 VOC <i>Europlus</i> Clear	MH2981, MH2982, MH2983	-	-	2:1	2.08 (249)

Additional Products (listing not intended to be all inclusive)		
SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacer (Aerosol)
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SX1047 High Build WB Flexible Surfacer
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)	SU470LV 1K Compliant Adhesion Promoter
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)	SXA1041 Bumper Black (Aerosol)

This "Yolo-Solano AQMD Rule 2.26 (PPG OMNI)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Yolo-Solano AQMD Rule 2.26 (PPG OMNI)" wall chart does not include all currently compliant OMNI products. The representative products listed are compliant with Yolo-Solano AQMD Rule 2.26 VOC limits as of the date of this wall chart; however, subsequent changes in Yolo-Solano AQMD Rule 2.26 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is NOT INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.