



Yolo-Solano County AQMD
Rule 2.26
Motor Vehicle and Mobile Equipment
Coating Operations
 Amended: 12/10/2008 | In Effect: 07/01/2010

Coating Category	lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts)			
Solvent (Surface Cleaner)	0.21 (25)* * VOC content value			
Pretreatment Coating/Wash Primer	5.5 (660)			
Primer/Primer Surfacer	2.1 (250)			
Primer Sealer	2.1 (250)			
Single-Stage Coating	2.8 (340)			
Color Coating	3.5 (420)			
Clear Coating	2.1 (250)			
Uniform Finish Coating	4.5 (540)			
Adhesion Promoter	4.5 (540)			
Product Code & Name		Reducer	Mix Ratio	VOC Content
Solvent (Substrate Cleaner)				Limit: 0.21 lbs/gal (25 g/L)
SWX350 H2O-SO-CLEAN® Wax & Grease Remover		-	-	0.17 (20)
CFX435LV - Low VOC Cleaner		Water	1 : 1	0.20 (25)
Product Code & Name	Hardener	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
Primer/Primer Surfacer				Limit: 2.1 lbs/gal (250 g/L)
F8801/WH/BK Thin Film Epoxy Primers	F8800	F8310	2 : 1 : 1/2	1.84 (221)
F8802/WH/BK Sandable Epoxy Primers	F8800	F8310	2 : 1 : 1/2	1.51 (181)
F8810/WH/BK Urethane Primers	F8204	F8311, F8312, or F8313	4 : 1 : 1	1.43 (171)
F8810/WH/BK Urethane Primers	F8200 or F8201	F8311, F8312, or F8313	8 : 1 : 2	1.43 (171)
F8811 Urethane Surfacer	F8204	F8311, F8312, or F8313	4 : 1 : 1	1.35 (162)
F8812/WH/BK Fast Dry Sealers	F8201	F8311	3 : 1 : 1	1.79 (215)
F8812/WH/BK Fast Dry Sealers	F8204	F8311	6 : 1 : 2	1.79 (215)
Product Code & Name	Hardener	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
Single-Stage Coating				Limit: 2.8 lbs/gal (340 g/L)
F1DG Ultra Low VOC Direct Gloss	F8200, F8201, or F8203	F8311, F8312, or F8313	2 : 1 : 1	1.46 (175)
F1M Ultra Low VOC Matte Topcoat	F8200	F8312 or F8313	3 : 1 : 1	1.50 (180)

Product Code & Name	Hardener	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
Color Coating				Limit: 3.5 lbs/gal (420 g/L)



Yolo-Solano County AQMD
Rule 2.26
Motor Vehicle and Mobile Equipment
Coating Operations
 Amended: 12/10/2008 | In Effect: 07/01/2010

F1BC Ultra Low VOC Basecoat	F8200, F8201, F8202, or F8203	F8311, F8312, or F8313	2 : 1 : 1	1.48 (177)
Product Code & Name	Hardener	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
Clear Coating				Limit: 2.1 lbs/gal (250 g/L)
F8600 Ultra Low VOC Repair Clearcoat	F8200 or F8201	F8311	3 : 1 : 1	1.36 (163)
F8600 Ultra Low VOC Repair Clearcoat	F8200 or F8201	F8314	3 : 1 : 1	1.89 (226)
F8605 Ultra Low VOC Clearcoat	F8200 or F8201	F8311	3 : 1 : 1	1.51 (181)
F8605 Ultra Low VOC Clearcoat	F8200 or F8201	F8314	3 : 1 : 1	2.01 (241)
Additional Products: (listing not intended to be all inclusive)				
F8720 Blending Clear	SU4901 Clean and Scuff Sponge		SXA840 Uniform Finish Blender (Aerosol)	
SLV840 Uniform Finish Blender	SU470LV 1K Compliant Adhesion Promoter			

Yolo-Solano AQMD Rule 2.26 – PPG DELFLEET ONE™

This “Yolo-Solano AQMD Rule 2.26 (PPG *Delfleet One*)” wall chart is intended to provide INFORMATION to PPG’s customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG’s products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This “Yolo-Solano AQMD Rule 2.26 (PPG *Delfleet One*)” wall chart does not include all currently compliant *Delfleet One* products. The representative products listed are compliant with Yolo-Solano AQMD Rule 2.26 VOC limits as of the date of this wall chart; however, subsequent changes in Yolo-Solano AQMD Rule 2.26 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.



PPG Industries
 Commercial Coatings
 19699 Progress Drive
 Strongsville, OH 44149
 1-800-647-6050

PPG Canada Inc.
 2301 Royal Windsor Drive, Unit #6
 Mississauga, Ontario L5J 1K5
 1-888-310-4762