

Eastern Kern APCD

Motor Vehicle and Mobile Equipment Refinishing Operations **Rule 410.4A**

ENVIROBASE® HIGH PERFORMANCE

Amended: 3/13/2014 | In Effect: 3/13/2014

Coating Category	Ibs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less E		
Solvent (Surface Cleaner)*	0.21 (25)		
Pretreatment Coating	5.5 (660)		
Primer / Primer Surfacer	2.1 (250)		
Primer Sealer	2.1 (250)		
Single Stage Coating	2.8 (340)		
Color Coating	3.5 (420)		
Underbody Coating	5.4 (650)		
Clear Coating	2.1 (250)		
Uniform Finish Coating	4.5 (540)		
Adhesion Promoter	4.5 (540)	*VOC content applies to this category only.	

Product Code & Name	Hardener/ Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				Limit: 0.21 lbs/gal (25 g/L)
SWX350 H ₂ O-SO-CLEAN [®] Wax & Grease Remover	-	-	-	0.17 (20)
SX1009 2.9 VOC Bug & Tar Remover*	-	-	-	2.89 (346)
SX330 Wax and Grease Remover*	-	-	-	6.31 (756)
SX394 1.4 Low VOC Cleaner*	-	-	-	1.34 (161)

*Rule 410.4A V. E allows the use of surface preparation solvents to clean plastic parts just prior to coating or VOC-containing materials for the removal of wax and grease provided that nonaerosol, hand-held spray bottles are used with a maximum solvent VOC content of 780 g/l and the total volume of the solvent does not exceed 20 gallons per year per facility. Records of solvent usage shall be kept in accordance with Section VII.C.4 of this rule.

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings			Limit: 5.5 lbs/gal (660 g/L)		
SX1071 ECOBASE [®] 5.5 Etch Prime	SX1072	-	-	1:1	5.48 (657)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer Surfacer				Lim	nit 2.1 lbs/gal (250 g/L)
ECP35 High Production Surfacer	EH391, EH392	ECRXX	-	4:1:1	1.71 (205)
ECP35 High Production Surfacer	EH391, EH392	ECRXX	SLV814	4:1:1:110%	1.67 (200)
DPLV Low VOC Epoxy Primer	DP401LV	DT18XX		2:1:1	1.16 (139)
EPW115 Waterborne Speed Prim	-	T494	-	1: 13%	0.72 (86)
NCP450 Iso-Free Primer	NCX455	DT18XX	-	4:1:1	1.33 (174)
Primer Sealer (apply over previously coat	ed surfaces)			Limi	it: 2.1 lbs/gal (250 g/L)
ECS2X A-Chromatic LV Sealer	EH391, EH392	D8764, D8774, D8767	-	4:1:1	2.05 (246)
ECS8X A-Chromatic LV Sealer	EH391, EH392	ECRXX, D87XX, DT18XX	-	4:1:1	2.07 (248)



Eastern Kern APCD

Motor Vehicle and Mobile Equipment Refinishing Operations Rule 410.4A

ENVIROBASE® HIGH PERFORMANCE

Amended: 3/13/2014 | In Effect: 3/13/2014

Product Code & Name	Hardener/Modifier/ Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt	
Basecoat for Multi Stage Topcoat System				Limit: 3.5 lbs/gal (420 g/L)		
Envirobase High Performance Basecoat	-	T494	-	100:10	3.33 (399)	
Envirobase High Performance Basecoat	-	T494	-	100:20	3.38 (405)	
Envirobase High Performance Basecoat	-	T494	-	100:30	3.50 (420)	
Envirobase High Performance Basecoat	-	-	T492	100:10	2.78 (333)	
Envirobase High Performance Basecoat	-	T494	T492	100:10:10	3.24 (388)	
Envirobase High Performance Basecoat	-	T494	T492	100:20:10	3.28 (393)	
Envirobase High Performance Basecoat	-	T494	T492	100:30:10	3.28 (393)	
Envirobase High Performance Basecoat	T493	T494	T492	100:5:10:10	3.21 (385)	
Envirobase High Performance Basecoat	T493	T494	T492	100:5:20:10	3.24 (388)	
Envirobase High Performance Basecoat	T493	T494	T492	100:5:30:10	3.25 (389)	
Envirobase High Performance Basecoat	T493	-	T492	100:5:10	2.81 (337)	
Underbody Coatings (Specialty)				Limit: 3.6 lbs/gal (430		
Internal Repair System	T581	T494	-	100:15:15	3.08 (369)	
Internal Repair System	T581	T494	-	100:15:20	3.09 (370)	
Clearcoat for Multi Stage Topcoat System				Limi	it: 2.1 lbs/gal (250 g/L)	
DC4125 Ceramiclear	DCH4126			2:1	2.05 (246)	
EC520 En-V ® High Production Clearcoat	ECH5075	ECRXX		3:1:1	2.07 (248)	
EC530 En-V Performance Clearcoa	ECH5075	ECRXX		3:1:1	1.94 (232)	
EC550 En-V Ultra Gloss Clearcoat	ECH5075	ECRXX		3:1:1	2.01 (241)	
EC800 Ultra Fast 2.1 Clearcoat	ECH8075 ECH8075	DT1855 ECA83		4:1:1 4:1:1	2.08 (249) 1.90 (228)	
EC5515 Low VOC Matte Clear	ECH5075	ECRXX, DT1585		3:1:1	2.02 (242)	
EC5517 Low VOC Semig-Gloss Clear	ECH5075	ECRXX, DT1585		3:1:1	2.02 (242)	
VC5250 DITZLER [®] Satin Clear	VH7250	DT18XX	-	4:1:1.5	1.86 (2.23)	
VC5700 Ditzler Custom Clear	VH7780, VH7795	DT1855	-	2:1:1	2.08 (249)	
Additional Products (listing not intended to	o be all inclusive)					
SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge		SXA1044 High	SXA1044 High Build Flexible Surfacer (Aerosol)		
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)		SXA1050 Plastic Adhesion Promoter (Aerosol)			
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner		SX1047 High Build WB Flexible Surfacer			
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)		SXA1041 Bumper Black (Aerosol)			
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)		SU470LV 1K Compliant Adhesion Promoter			

This "Eastern Kern County APCD Rule 410.4A PPG Envirobase High Performance" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Eastern Kern APCD Rule 410.4A PPG Envirobase High Performance" wall chart does not include all currently compliant PPG Envirobase High Performance products. The representative products listed are compliant with Eastern Kern APCD Rule 410.4A VOC limits as of the date of this wall chart; however, subsequent changes in Eastern Kern APCD Rule 410.4A PQ Limits, as of the date of this wall chart; however, subsequent changes in Eastern Kern APCD Rule 410.4A PQ Limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.