



Delivering a balance of performance and value



PPG POWERCRON® 6100HE high-edge cationic epoxy electrocoat

Powercron 6100HE electrocoat uses high-performance cationic epoxy technology that provides excellent edge coverage with the added benefit of an improved surface profile.

The PPG Benefit



Two-component feed package with metal-based catalyst



Exceptional throwpower and uniform, high-edge coverage of complex parts



VOCs < 0.3 lbs./gal. (36 g/L) as supplied



Available in multiple colors (not controlled)



0.5 – 1.5 mils recommended film build



Low-cure bake 350° F (177° C) for 20 minutes may provide natural gas cost savings



Major OEM approvals simplify specification process and broaden potential customer base



Torque-modified formulations available

Edge corrosion test

Coated, laser-cut panels are placed in a five-percent salt-spray cabinet for 720 hours and rust spots are counted along the sharp edges.



Powercron 6100 HE electrocoat:

- 6-10 rust spots
- <0.5% edge corrosion

Competitor's electrocoat:

- 50-60 rust spots
- >50% edge corrosion

Relative coating performance

Best: High Performance	POWERCRON® ADVANTEDGE™
Better: Balanced	FRAMECOAT® II POWERCRON® 6100HE
Good: Value	POWERCRON® 6000CX

Suggested industries

Automotive parts and accessories

General industrial

Heavy duty equipment

Transportation



This document contains general information only and should not be construed as creating any warranties, express or implied. Please contact a PPG representative for additional information.

The PPG Logo, We protect and beautify the world, FrameCoat and Powercron are registered trademarks and Advantedge is a trademark of PPG Industries Ohio, Inc. The IN Logo is a registered trademark of LinkedIn Corporation. ©2023 PPG Industries, Inc. All rights reserved. 04/23 IC135

PPG Industrial Coatings • One PPG Place, Pittsburgh, PA 15272 • 1.888.774.2001 • ppg.com/industrialcoatings



We protect and beautify the world®