

Thinner Selection Guide



The below recommendations are only a general reference and should be used solely as a starting point for choosing the appropriate reducer. Your particular spray environment and job size may require slight adjustments. Please see product data sheets for additional information.

| Compatible Products | Ambient Air Temperature | | | | | | | |
|--|-------------------------|------------------------------|--------------------------------|--------------------------|------------------------------|------------------------|------------------------------------|------------------------------|
| | 60° F (16° C) | 65° F (18° C) | 70° F (21° C) | 75° F (24° C) | 80° F (27° C) | 85° F (29° C) | 90° F (32° C) | 95° F (35° C) |
| Primers <ul style="list-style-type: none"> VP2X0 2K Urethane Primer Surfer VS3X0 2K Urethane Primer Sealer | | VR251 Fast Thinner | | | | | | |
| | | | VR252 Medium Thinner | | | | | |
| | | | | | VR253 Slow Thinner | | | |
| | | | | | | | VR254 Very Slow Thinner | |
| Basecoat <ul style="list-style-type: none"> VB Basecoat | | VR151 Universal Fast Thinner | | | | | | |
| | | | VR152 Universal Normal Thinner | | | | | |
| | | | | | VR153 Universal Slow Thinner | | | |
| | | | | | | | VR154 Universal Extra Slow Thinner | |
| Clearcoats <ul style="list-style-type: none"> VC850 Matte / VC800 Semi-Gloss Clearcoat System (VR35X Thinners) VC300 UHS Clear (VR55X Thinners) | | VR351 UHS Fast Thinner | | | | | | |
| | | | | VR352 UHS Normal Thinner | | | | |
| | | | | | | VR353 UHS Slow Thinner | | |
| | | VR551 HP Normal Thinner | | | | | | VR354 UHS Extra Slow Thinner |
| | | | | | VR552 HP Slow Thinner | | | |

TIPS

- A higher-temperature reducer in a clearcoat will allow the surface to stay open longer and provide additional leveling.
- Consider the job size when selecting the appropriate reducer. Larger jobs may require a higher-temperature reducer in order to maintain a “wet” edge.

WARNING: Certain products listed may contain chemicals known to the State of California to cause cancer and/or reproductive harm. For more information go to P65Warnings.ca.gov.

The PPG Logo, We protect and beautify the world and Velocity are registered trademarks of PPG Industries Ohio, Inc. The Facebook “f” Logo is a registered trademark of Facebook, Inc. The IN Logo is a registered trademark of LinkedIn Corporation. The Instagram Glyph is a registered trademark of Instagram, LLC. ©2025 PPG Industries, Inc. 07/25 VL-TSG

PPG Automotive Refinish • 19699 Progress Drive, Strongsville, OH 44149 • 1.800.647.6050 • ppg.com/refinish [f](#) [in](#) [ig](#)



We protect and beautify the world®