



San Luis Obispo County APCD

Motor Vehicle and Mobile Equipment Coating Operations



Rule 423

Amended: 11/19/2008 | In Effect: 7/1/2010

| Coating Category | lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts). |
|----------------------------|---|
| Solvent (Surface Cleaner)* | 0.21 (25) |
| Pretreatment Coating | 5.5 (660) |
| Primer / Primer Surfacer | 2.1 (250) |
| Primer Sealer | 2.1 (250) |
| Single Stage Coating | 2.8 (340) |
| Color Coating | 3.5 (420) |
| Underbody Coating | 3.6 (430) |
| Clear Coating | 2.1 (250) |
| Uniform Finish Coating | 4.5 (540) |
| Adhesion Promoter | 4.5 (540) |

*VOC content value.

| Product Code & Name | Hardener/ Activator | Reducer | Mix Ratio | VOC Content |
|--|------------------------|---------|-----------|-------------------------------------|
| Solvent (Surface Cleaner) | | | | Limit: 0.21 lbs/gal (25 g/L) |
| SWX350 H ₂ O-SO-CLEAN [®] Wax and Grease Remover | - | - | - | 0.17 (20) |
| SX1009 2.9 VOC Bug and Tar Remover* | - | - | - | 2.89 (346) |
| SX103 MULTI-PREP [®] Cleaner* | - | - | - | 6.48 (777) |
| SX330 ACRYLI-CLEAN [®] Wax and Grease Remover* | - | - | - | 6.36 (762) |
| SX394 1.4 Low VOC Cleaner* | - | - | - | 1.32 (158) |

*Rule 423 (C.) (7.) Allows exemption only in hand-held, non-aerosol bottles, max. VOC content 6.5 lbs./gal (780g/L), and no more than 20 gal/year/facility. Recordkeeping required.

| Product Code & Name | Hardener/Activator | Reducer | Additives | Mix Ratio | Applied VOC Less Water Less Exempt |
|--|--------------------|---------------------|-----------|-------------|---------------------------------------|
| Pre-Treatment Coatings | | | | | Limit: 5.5 lbs/gal (660 g/L) |
| SX1071 ECOBASE [®] 5.5 Etch Prime | SX1072 | - | - | 1:1 | 5.48 (657) |
| SXA1031 Etch Primer - Gray | - | - | - | Aerosol | N/A |
| Primer Surfacer | | | | | Limit 2.1 lbs/gal (250 g/L) |
| SUA1080 UV Primer | - | - | - | Aerosol | N/A |
| ECP1X A-Chromatic Surfacer | EH391 | D8764, D8774, D8767 | - | 4:1:1 | 2.08 (249) |
| ECP1X A-Chromatic Surfacer | EH391 | D8764, D8774, D8767 | - | 4:1 | 2.08 (249) |
| ECP1X A-Chromatic Surfacer | EH391 | D8764, D8774, D8767 | SL93LV | 4:1:1 + 10% | 2.09 (250) |
| DPXXLV 2.1 Epoxy Primer | DP401LV | D8764, D8774, D8767 | - | 2:1:1 | 2.09 (250) |
| Primer Sealer (apply over previously coated surfaces) | | | | | Limit: 2.1 lbs/gal (250 g/L) |
| ECS2X A-Chromatic LV Sealer | EH391, EH392 | D8764, D8774, D8767 | - | 4:1:1 | 2.05 (246) |
| Single Stage Coating | | | | | Limit: 2.8 lbs/gal (340 g/L) |
| ENVIROBASE [®] Interior System | T584 | T494 | - | 100:15:15 | 2.79 (334) |
| Basecoat for Multi Stage Topcoat System | | | | | Limit: 3.5 lbs/gal (420 g/L) |
| Envirobase High Performance Basecoat | - | T494 | - | 100:10 | 3.33 (399) |
| Envirobase High Performance Basecoat | - | T494 | - | 100:20 | 3.38 (405) |
| Envirobase High Performance Basecoat | - | T494 | - | 100:30 | 3.50 (419) |
| Envirobase High Performance Basecoat | - | - | T492 | 100:10 | 2.78 (333) |
| Envirobase High Performance Basecoat | - | T494 | T492 | 100:10:10 | 3.24 (388) |
| Envirobase High Performance Basecoat | - | T494 | T492 | 100:20:10 | 3.28 (393) |
| Envirobase High Performance Basecoat | - | T494 | T492 | 100:30:10 | 3.28 (393) |



San Luis Obispo County APCD

Motor Vehicle and Mobile Equipment Coating Operations



Rule 423

Amended: 11/19/2008 | In Effect: 7/1/2010

| Product Code & Name | Hardener/Activator | Reducer | Additives | Mix Ratio | Applied VOC Less Water Less Exempt |
|---|------------------------------|-----------------------------|-----------|----------------|---------------------------------------|
| Basecoat for Multi Stage Topcoat System | | | | | Limit: 3.5 lbs/gal (420 g/L) |
| Envirobase High Performance Basecoat | T493 | T494 | T492 | 100:5:10:10 | 3.21 (385) |
| Envirobase High Performance Basecoat | T493 | T494 | T492 | 100:5:20:10 | 3.24 (388) |
| Envirobase High Performance Basecoat | T493 | T494 | T492 | 100:5:30:10 | 3.25 (389) |
| Envirobase High Performance Basecoat | T493 | - | T492 | 100:5:10 | 2.81 (337) |
| Underbody Coatings (Specialty) | | | | | Limit: 3.6 lbs/gal (430 g/L) |
| Internal Repair System | T581 | T494 | - | 100:15:15 | 3.08 (369) |
| Internal Repair System | T581 | T494 | - | 100:15:20 | 3.09 (370) |
| Clearcoat for Multi Stage Topcoat System | | | | | Limit: 2.1 lbs/gal (250 g/L) |
| D8126 CERAMICLEAR® | D8226 | - | - | 2:1 | 2.00 (240) |
| D8188 Glamour LV Clearcoat | D8382, D8383 D8384, D8385 | D8767 | - | 3:1:10% | 2.05 (246) |
| EC520 En-V ® High Production Clearcoat | ECH5075 | ECRXX | - | 3:1:1 | 2.07 (248) |
| EC530 En-V Performance Clearcoat | ECH5075 | ECRXX | - | 3:1:1 | 1.94 (232) |
| EC550 En-V Ultra Gloss Clearcoat | ECH5075 | ECRXX | - | 3:1:1 | 2.01 (241) |
| EC700 ONE VISIT® Production Clear | ECH7070, 7080, 7090 | - | - | 4:1 | 2.08 (249) |
| EC700 <i>One Visit</i> Production Clear | ECH7070, 7080, 7090 | D87XX | SL93LV | 4:0.5:1:2% | 2.09 (250) |
| EC750 <i>One Visit</i> Appearance Clear | ECH7070, 7080, 7090 | - | - | 4:1 | 2.08 (249) |
| EC800 Ultra Fast 2.1 Clearcoat | ECH8075 ECH8075 | D8767, DT1855 ECA83 | - - | 4:1:1 4:1:1 | 2.08 (249) 1.90 (228) |
| ECW8186 Waterborne Clearcoat | EHW8224 | T494 | - | 5:2:2 | 2.09 (250) |
| VC5250 DITZLER® Satin Clear | VH7250 | DT18XX, D87XX, P850-1775 | - | 4:1:1.5 | 1.85 (222) |
| VC5700 <i>Ditzler</i> Custom Clear | VH7780, VH7795 | DT1855, D8767, P850-1775 | - | 2:1:1 | 2.08 (249) |

| Additional Products (listing not intended to be all inclusive) | | |
|---|---|---|
| SLV4985 Universal Flattening Agent | SLV898 Retarder | SWX100 Waterborne Gun Cleaner |
| SLV73 Fisheye Eliminator | SU470LV 1K Compliant Adhesion Promoter | SXA840 Uniform Finish Blender (Aerosol) |
| SLV814 Universal Flexibilizer | SU4901 Clean and Scuff Sponge | SXA1030 Black Guide Coat (Aerosol) |
| SLV840 Uniform Finish Blender | SUA4903 Advanced Plastic Bond (Aerosol) | SXA1041 Bumper Black (Aerosol) |

This "San Luis Obispo Rule 423 (PPG Global)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "San Luis Obispo Rule 423 (PPG Global)" wall chart does not include all currently compliant *Global* products. The representative products listed are compliant with San Luis Obispo Rule 423 VOC limits as of the date of this wall chart; however, subsequent changes in the San Luis Obispo Rule 423 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

The PPG logo, *Global Refinish System*, *H2O-So-Clean*, *Multi-Prep*, *Ecobase*, *Acryli-Clean*, *Ceramiclear*, *En-V*, *One-Visit*, *Ditzler*, and *Envirobase* are trademarks of PPG Industries of Ohio, Inc.