



## DX101 Sanding Paste

DX101 Final Scuff is a sanding paste designed to assist the technician in thoroughly and quickly prepping a surface to be painted or blended.

### **SURFACE PREPARATION**

The surface should be washed with soap and water and thoroughly flushed with clean water and wiped dry before applying DX101. Panels should be cleaned with D837 Spirit Wipe or D846 Degreasing and Anti-Static Agent for Plastics.

### **APPLICATION**

1. Dampen a fine abrasive scuff pad with water.
2. Apply a small amount of DX101 (size of a quarter or less) to the pad.
3. Using the pad, abrade the surface completely. Reapply water and DX101 as needed.
4. Thoroughly rinse the surface with clean water. Wipe off any remaining DX101 from the surface, making certain that all DX101 is removed from the entire panel.
5. Final clean the surface with D837 Spirit Wipe. Plastic substrates should be cleaned with D846 Degreasing and Anti-Static Agent for Plastics.

**NOTE:** Make certain to knead the tube of DX101 to thoroughly mix all ingredients prior to each use. DX101 will abrade and de-gloss the surface with minimal hand pressure, thus eliminating potential scratches caused by using a dry abrasive pad alone. Do not allow DX101 to freeze. DX101 produces a sand scratch pattern equivalent to 1500 – 1800 grit.