



State of Delaware
 Mobile Equipment Repair and Refinishing
Title 7 Regulation 1124 Section 11.0
 Amended: 10/11/2010 | In Effect: 1/1/2012



Coating Category	lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).	
Solvent (Surface Cleaner)*	0.21 (25)	*VOC content applies to this category only
Pretreatment Coating	5.5 (660)	
Primer / Primer Surfacer	2.1 (250)	
Primer Sealer	2.1 (250)	
Single Stage Coating	2.8 (340)	
Color Coating	3.5 (420)	
Underbody Coating	3.6 (430)	
Clear Coating	2.1 (250)	
Adhesion Promoter	4.5 (540)	

Product Code & Name	Hardener/Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				Limit: 0.21 lbs/gal (25 g/L)
SWX350 H ₂ O-SO-CLEAN [®] Wax and Grease Remover	-	-	-	0.17 (20)
SX1009 2.9 VOC Bug and Tar Remover*	-	-	-	2.89 (346)

*11.3.2.1 Special cleaning solvent for use in specific and difficult cleaning tasks associated with surface preparation with VOC content no greater than 350 g/L may be used at a volume equal to 2.5% of the preceding year's annual coating usage up to a maximum of 40 gallons per year.

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings					Limit: 5.5 lbs/gal (660 g/L)
SX1071 ECOBASE [®] 5.5 Etch Prime	SX1072	-	-	1:1	5.48 (657)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer Surfacer					Limit 2.1 lbs/gal (250 g/L)
JP209 Gray Polyester Primer / Filler	MEKP	-	-	0.5 oz. per quart	0.98 (118)
JP35X 2.1 VOC Multi-Purpose Primer	JH358	JR55X	-	4:1:2	2.05 (246)
JP390 2.1 VOC Epoxy Primer - Gray	JH397	JR55X	-	2:1:1	2.07 (248)
Primer Sealer (apply over previously coated surfaces)					Limit: 2.1 lbs/gal (250 g/L)
JP35X 2.1 VOC Multi-Purpose Primer	JH358	JR55X	JC78x, or JC7200	3:1:1:1	2.09 (250)
JP36X Series 2.1 VOC Urethane Sealers	JH358	JR55X	-	4:1:1	2.09 (250)
JP390 2.1 VOC Epoxy Primer - Gray	JH397	JR55X	-	2:1:2	2.07 (248)
Single Stage Coating					Limit: 2.8 lbs/gal (340 g/L)
JTX 2.8 VOC Direct Gloss Acrylic Urethane	JH6028	JR55X	-	4:1:2	2.80 (335)
JLX 2.8 VOC Acrylic Enamel	JH6028	JR55X	-	4:1:1	2.76 (331)
Basecoat for Multi Stage Topcoat System					Limit: 3.5 lbs/gal (420 g/L)
JBX 3.5 Acrylic Basecoat	-	JR29X	-	1:1	3.48 (417)
<i>Use JBPX blend to spray mix recommendation without JH6028 only with new color formulas that contain J179</i>					
JBPX 3.5 VOC Acrylic Urethane Basecoat	-	JR55X	-	1:1	3.49 (419)
<i>Use JBPX blend to spray mix recommendations with JH6028 with all historic color formulas that contain J136</i>					
JBPX 3.5 VOC Acrylic Urethane Basecoat	JH6028	JR55X	-	10:1:10	3.48 (417)
JBPX 3.5 VOC Acrylic Urethane Basecoat	JH6028	JR55X	-	10:1:5	3.48 (417)



State of Delaware
 Mobile Equipment Repair and Refinishing
Title 7 Regulation 1124 Section 11.0
 Amended: 10/11/2010 | In Effect: 1/1/2012



Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Clear Coating					Limit: 2.1 lbs/gal (250 g/L)
JC780 2.1 VOC Polyurethane Speed Clear	JH7870, JH7880, JH7890	-	-	4:1	2.08 (249)
JC781 2.1 VOC Polyurethane High Gloss Clear	JH7870, JH7880, JH7890	-	-	4:1	2.06 (247)
JC830 2.1 VOC Production Clear	JH8370, JH8380, JH8390	JR555, JR556	-	4:1:0.5	2.08 (249)
JC7100 2.1 VOC HS European Multi-Panel Clearcoat	JH7121, JH7131	-	-	2:1	1.95 (234)
JC7200 2.1 VOC European Clearcoat	JH72XX	-	-	2:1	2.08 (249)

Additional Products (listing not intended to be all inclusive)		
SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacers (Aerosol)
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SX1047 High Build WB Flexible Surfacers
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)	SU470LV 1K Compliant Adhesion Promoter
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)	SXA1041 Bumper Black (Aerosol)

This "State of Delaware Title 7 Regulation 1124 Section 11.0 (PPG Shop-Line)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "State of Delaware Title 7 Regulation 1124 Section 11.0 (PPG Shop-Line)" wall chart does not include all currently compliant Shop-Line products. The representative products listed are compliant with State of Delaware Title 7 Regulation 1124 Section 11.0 VOC limits as of the date of this wall chart; however, subsequent changes in State of Delaware Title 7 Regulation 1124 Section 11.0 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.