



State of Utah

Utah R307-354 Automotive Refinish Coatings

Cache, Davis, Salt Lake, Utah and Weber Counties with a PTE above 2.7 tons per year (tpy), new & existing sources. Box, Elder and Toole Counties with a PTE above 2.7 tpy for new sources - startup after 2/1/14 & 5.0 tpy for existing sources in operation before 2/1/14.

The above listed sources must comply as of July 1, 2014



Coating Category	lbs/gal (g/L)	Limit: VOC Regulatory (Less Water Less Exempts)			
Pretreatments Coating	5.5 (660)	* VOC content applies to this category only			
Primer/Primer Surfacer	2.1 (250)				
Primer Sealer	2.1 (250)				
Single-Stage Coating	2.8 (340)				
Color Coating	3.5 (420)				
Clear Coating	2.1 (250)				
Adhesion Promoter	4.5 (540)				
Product Code & Name	Reducer	Mix Ratio	VOC content		
Solvent (Substrate Cleaner)				Limit: N/A	
CFX435LV - Low VOC Cleaner	water	1 : 1	0.21 (25)		
CFX436 Wax and Grease Remover	-	as is	6.36 (762)		
DX103 Multi-Prep	-	as is	6.48 (777)		
SXA330 Wax & Grease Remover	-	Aerosol	5.77 (691)		
SXA103 Multi-Prep Cleaner (Plastic only)	-	Aerosol	5.88 (705)		
Product Code & Name	Hardener/Activator	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt	
Pretreatment Coating				Limit: 5.5 lbs/gal (660 g/L)	
F4945 5.5 VOC Wash Primer	F4946	-	1 : 1	5.32 (637)	
SXA1031 Etch Primer – Gray	-	-	Aerosol	N/A	
Product Code & Name	Hardener/Activator	Additives	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
Primer/Primer Surfacer					Limit: 2.1 lbs/gal (250 g/L)
ESU410 2.1/2.8 Polyurethane Primer	ESU419	ESX590	-	5 : 1 + 6 oz / RTS gal	1.99 (238)
ESU470 2.1 VOC Wet on Wet Epoxy Primer - Gray	ESU479	-	ESR300 or ESR310	2 : 1 : 1 or 2 : 1 : 2 (reducer last)	2.07 (248)
ESU480/481/482 2.1 VOC Epoxy Primer	ESU489	-	-	4 : 1	2.09 (250)
F3970/BKWH Ultra High Solids Primer	F3971	F3400 or F3405	F3385, F3390 or F3395	3 : 1 + 6 oz / RTS gal + 10% optional reducer	2.07 (248)
F3998 2.1 VOC Primer Surfacer	F3999	-	-	2 : 1	1.99 (238)
F4921/BKWH 2.1 VOC Epoxy Primer	F4922	-	F3385, F3390 or F3395	3 : 1 : 1	2.05 (246)
F4932/BKWH 2.1 VOC Fast Dry Urethane Surfacer	F4933	-	F3385, F3390 or F3395	4 : 1 : 1	2.08 (249)
F4935/36/37 High Solids Epoxy Primers	F4938	-	-	1 : 1	2.08 (249)
Single-Stage Coating				Limit: 2.84 lbs/gal (340 g/L)	
ESSS Single Stage Polyurethane Enamel	ESH200	ESX5XX	-	6 : 1 : 1	2.76 (331)
FDGU Single Stage Ultra high Solids Polyurethane Enamel	F3260	F3400, F3405 or F3410	F3385, F3390 or F3395	3 : 1 + 6 oz /RTS gal + 10% reducer	2.82 (338)
FDSU Ultra HS Polyurethane Single Stage	F3260	F3400, F3405 or F3410	F3385, F3390 or F3395	3 : 1 + 6 oz /RTS gal + 10% reducer	2.82 (338)

Utah State Rule 307-354 – PPG DELFLEET® Evolution and DELFLEET ESSENTIAL®



State of Utah

Utah R307-354 Automotive Refinish Coatings

Cache, Davis, Salt Lake, Utah and Weber Counties with a PTE above 2.7 tons per year (tpy), new & existing sources. Box, Elder and Toole Counties with a PTE above 2.7 tpy for new sources - startup after 2/1/14 & 5.0 tpy for existing sources in operation before 2/1/14.

The above listed sources must comply as of July 1, 2014



Product Code & Name	Hardener/Activator	Additives	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
Color Coating					Limit: 3.5 lbs/gal (420 g/L)
ESSS Basecoat Polyurethane Basecoat	ESH210	ESB800	-	2 : 1 : 1	3.04 (364)
FBCH High Solids Polyurethane Basecoat	F3200 or F3260	F3440, F3441 or F3442	-	3 : 1 : 1	3.47 (416)
FBCS High Solids Basecoat - Fast	F3200, F3259 or F3260-	-	F3385	3 : 1 + 10%	3.04 (364)
FBCS High Solids Basecoat - Fast	F3200 or F3260-	-	F3330, F3340, F3350 or F3360	3 : 1 + 10%	3.41 (409)
Clear Coating					Limit: 2.1 lbs/gal (250 g/L)
ESC621 2.1 VOC Clearcoat	ESH200	-	ESX711, ESX721, ESR300 or ESR310	4 : 1 : 1	2.06 (247)
F3921 2.1 VOC Clearcoat	F3210 or F3211	-	F3385, F3390 or F3395	3 : 1 : 1/2	2.05 (246)
Additional Products: (listing not intended to be all inclusive)					
FBCH500 FBCH Blending Clear	SU4901 Clean and Scuff Sponge		SXA840 Blending Solvent		
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond				

Utah State Rule 307-354 – PPG DELFLEET® Evolution and DELFLEET ESSENTIAL®

This "Utah R307-354 Automotive Refinish Coatings (PPG Delfleet)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Utah R307-354 (PPG Delfleet)" wall chart does not include all currently compliant Delfleet products. The representative products listed are compliant with R307-354 VOC limits as of the date of this wall chart; however, subsequent changes in R307-354 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.



PPG Industries, Inc.
Commercial Coatings
19699 Progress Drive
Strongsville, OH 44149
1-800-647-6050

PPG Canada Inc.
Commercial Coatings
2301 Royal Windsor Drive, Unit #6
Mississauga, Ontario L5J 1K5
1-888-310-4762