



Utah R307-354 Automotive Refinish Coatings



Cache, Davis, Salt Lake, Utah and Weber Counties with a PTE above 2.7 tons per year (tpy), new & existing sources. Box, Elder and Toole Counties with a PTE above 2.7 tpy for new sources - startup after 2/1/14 & 5.0 tpy for existing sources in operation before 2/1/14.

Coating Category	lbs/gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).
Solvent (Surface Cleaner)	N/A
Pretreatment Coating	5.5 (660)
Primer / Primer Surfacer	2.1 (250)
Primer Sealer	2.1 (250)
Single Stage Coating	2.8 (340)
Color Coating	3.5 (420)
Underbody Coating	3.6 (430)
Clear Coating	2.1 (250)
Uniform Finish Coating	4.5 (540)
Adhesion Promoter	4.5 (540)

Product Code & Name	Hardener/Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				Limit: N/A
SWX350 H2O-So-Clean Wax & Grease Remover	-	-	-	0.17 (20)
SWX360 Waterborne Pre-Cleaner	-	water	1:2	0.20 (24)
SX1005 Low VOC Wax and Grease Remover	-	water	1:1	0.21 (25)
SX1009 2.9 VOC Bug & Tar Remover	-	-	-	2.89 (346)
DX330 Wax & Grease Remover	-	-	-	6.36 (762)

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pretreatment Coatings					Limit: 5.5 lbs/gal (660 g/L)
SX1071 Etch Prime	SX1072	-	-	1:1	5.48 (657)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer / Primer Surfacer					Limit: 2.1 lbs/gal (250 g/L)
DPLV 305X Acrylic Urethane Surfacer	DHLV3030	DT18XX Series	-	4:1:1	2.03 (243)
DPLV 305X Acrylic Urethane Surfacer	DHLV3030	-	-	4:1	2.03 (243)
DPLV 2.1 Epoxy Primer	DP401LV	DT18XX Series	-	2:1:1	2.09 (250)
DS1002 UV Cured Primer Surfacer	-	-	-	Aerosol	N/A
ECP1X A-Chromatic Surfacer	EH391	DT18XX Series	-	4:1:1	2.09 (250)
ECP1X A-Chromatic Surfacer	EH391	DT18XX Series	-	4:1	2.08 (249)
ECP1X A-Chromatic Surfacer	EH391	DT18XX Series	EA157	4:1:1 + 10%	2.09 (250)
EPW115 Waterborne Speed Prime		T494		1:13%	.72 (86)
NCP280 2.1 VOC Primer Surfacer	NCX285			2:1	2.10 (250)
NCP280 2.1 VOC Primer Surfacer	NCX285			2:1+10% Acetone	2.1 (250)
Primer Sealer (apply over previously coated surfaces)					Limit: 2.1 lbs/gal (250 g/L)
ECS2X A-Chromatic LV Sealer	EH391	DT18XX Series	-	4:1:1	1.82 (246)
Single Stage Coating					Limit: 2.8 lbs/gal (250 g/L)
ENVIROBASE® Interior System	T584	T494	-	100:15:15	2.79 (334)



Utah R307-354 Automotive Refinish Coatings

Cache, Davis, Salt Lake, Utah and Weber Counties with a PTE above 2.7 tons per year (tpy), new & existing sources. Box, Elder and Toole Counties with a PTE above 2.7 tpy for new sources - startup after 2/1/14 & 5.0 tpy for existing sources in operation before 2/1/14.



Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Color Coating					Limit: 3.5 lbs/gal (420 g/L)
Envirobase Waterborne Basecoat	-	T494	-	100:10	3.35 (401)
Envirobase Waterborne Basecoat	-	T494	-	100:20	3.40 (407)
Envirobase Waterborne Basecoat	-	T494	-	100:30	3.50 (419)
Envirobase Waterborne Basecoat	-	-	T492	100:10	3.36 (403)
Envirobase Waterborne Basecoat	-	T494	T492	100:10:10	3.38 (405)
Envirobase Waterborne Basecoat	-	T494	T492	100:20:10	3.40 (407)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:10	3.05 (336)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:20	3.09 (370)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:30	3.11 (373)
Underbody Coating					Limit: 3.6 lbs/gal (430 g/L)
Envirobase Internal Repair System	T581	T494	-	100:15:15	3.08 (369)
Clear Coating					Limit: 2.1 lbs/gal (250 g/L)
DC3010 DELTRON® High Velocity Clear	DCH36XX	-	-	2:1	2.00 (240)
DC4010 Velocity Premium Clear	DCH36XX	D8767	-	3:1:10%	2.05 (246)
DC4010 Velocity Premium Clear	DCH36XX	-	-	4:1	2.08 (249)
DCU2010 2.1 Speed Clear	DCX20XX	-	-	2:1	2.05 (246)
DC4125 Ceramiclear	DCH4126	-	-	4:1	2.07 (248)
EC700 OneVisit Production Clear	ECH70XX	-	-	4:1	2.08 (249)
EC700 OneVisit Production Clear	ECH70XX	D87XX	EA10	4:1:0.5 +5%	2.08 (249)
EC750 OneVisit Appearance Clear	ECH70XX	-	-	4:1	2.08 (249)
EC800 Ultra Fast 2.1 Clearcoat	ECH8075	D8767, DT1855	-	4:1:1	2.08 (249)
	ECH8075	ECA83	-	4:1:1	1.90 (228)

Additional Products (listing not intended to be all inclusive)

SLV4985 Universal Flattening Agent	SU460LV 1K Compliant Adhesion Promoter	SX1047 High Build Flexible Surfacer
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond	DX310 EZ Cleaner
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	DX101 Sanding Paste
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender	SXA1041 Bumper Black
SU4901 Clean and Scuff Sponge	SXA1030 Black Guide Coat	
DX310 EZ Cleaner	SXA1033 Texture Spray	

This "Bay Area AQMD Regulation 8 Rule 45 (PPG Deltron)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Bay Area AQMD Regulation 8 Rule 45 (PPG Deltron)" wall chart does not include all currently compliant Deltron products. The representative products listed are compliant with Bay Area AQMD Regulation 8 Rule 45 VOC limits as of the date of this wall chart; however, subsequent changes in Bay Area AQMD Regulation 8 Rule 45 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.