



**San Joaquin Valley APCD**  
**Rule 4612**  
**Motor Vehicle and Mobile Equipment**  
**Coating Operations**  
 Amended: 10/21/2010 | In Effect: 10/21/2010

| Coating Category                          | lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts) |                              |             |  |
|---|--|------------------------------|-------------|--|
| Solvent (Surface Cleaner)                 | 0.21 (25)* * VOC content value                                     |                              |             |  |
| Pretreatment Coating/Wash Primer          | 5.5 (660)  |                              |             |  |
| Primer/Primer Surfacer                    | 2.1 (250)  |                              |             |  |
| Primer Sealer                             | 2.1 (250)  |                              |             |  |
| Single-Stage Coating                      | 2.8 (340)  |                              |             |  |
| Color Coating                             | 3.5 (420)  |                              |             |  |
| Clear Coating                             | 2.1 (250)  |                              |             |  |
| Uniform Finish Coating                    | 4.5 (540)  |                              |             |  |
| Adhesion Promoter                         | 4.5 (540)  |                              |             |  |
| Product Code & Name                       |  | Reducer                      | Mix Ratio   | VOC Content                              |
| Solvent (Substrate Cleaner)               |  |                              |             | Limit: 0.21 lbs/gal (25 g/L)             |
| SWX350 H2O-SO-CLEAN® Wax & Grease Remover |  | -                            | -           | 0.17 (20)                                |
| CFX435LV - Low VOC Cleaner                |  | Water                        | 1 : 1       | 0.20 (25)                                |
| SX1009 2.9 VOC Bug and Tar Remover*       |  | -                            | -           | 2.89 (346)                               |
| * Allows UNDER Rule 4612 section 5.8.2    |  |                              |             |  |
| Product Code & Name                       | Hardener   | Reducer                      | Mix Ratio   | Applied VOC<br>Less Water<br>Less Exempt |
| Primer/Primer Surfacer                    |  |                              |             | Limit: 2.1 lbs/gal (250 g/L)             |
| F8801/WH/BK Thin Film Epoxy Primers       | F8800  | F8310                        | 2 : 1 : 1/2 | 1.84 (221)                               |
| F8802/WH/BK Sandable Epoxy Primers        | F8800  | F8310                        | 2 : 1 : 1/2 | 1.51 (181)                               |
| F8810/WH/BK Urethane Primers              | F8204  | F8311,<br>F8312, or<br>F8313 | 4 : 1 : 1   | 1.43 (171)                               |
| F8810/WH/BK Urethane Primers              | F8200 or F8201   | F8311,<br>F8312, or<br>F8313 | 8 : 1 : 2   | 1.43 (171)                               |
| F8811 Urethane Surfacer                   | F8204  | F8311,<br>F8312, or<br>F8313 | 4 : 1 : 1   | 1.35 (162)                               |
| F8812/WH/BK Fast Dry Sealers              | F8201  | F8311                        | 3 : 1 : 1   | 1.79 (215)                               |
| F8812/WH/BK Fast Dry Sealers              | F8204  | F8311                        | 6 : 1 : 2   | 1.79 (215)                               |
| Product Code & Name                       | Hardener   | Reducer                      | Mix Ratio   | Applied VOC<br>Less Water<br>Less Exempt |
| Single-Stage Coating                      |  |                              |             | Limit: 2.8 lbs/gal (340 g/L)             |
| F1DG Ultra Low VOC Direct Gloss           | F8200, F8201,<br>or F8203  | F8311,<br>F8312, or<br>F8313 | 2 : 1 : 1   | 1.46 (175)                               |
| F1M Ultra Low VOC Matte Topcoat           | F8200  | F8312 or<br>F8313            | 3 : 1 : 1   | 1.50 (180)                               |



**San Joaquin Valley APCD**  
**Rule 4612**  
**Motor Vehicle and Mobile Equipment**  
**Coating Operations**  
 Amended: 10/21/2010 | In Effect: 10/21/2010

| Product Code & Name  | Hardener                               | Reducer                      | Mix Ratio                                  | Applied VOC<br>Less Water<br>Less Exempt |
|--|--|------------------------------|--|--|
| <b>Color Coating</b>   |  |                              |  | <b>Limit: 3.5 lbs/gal (420 g/L)</b>      |
| F1BC Ultra Low VOC Basecoat  | F8200, F8201,<br>F8202, or F8203       | F8311,<br>F8312, or<br>F8313 | 2 : 1 : 1                                  | 1.48 (177)                               |
| Product Code & Name  | Hardener                               | Reducer                      | Mix Ratio                                  | Applied VOC<br>Less Water<br>Less Exempt |
| <b>Clear Coating</b>   |  |                              |  | <b>Limit: 2.1 lbs/gal (250 g/L)</b>      |
| F8600 Ultra Low VOC Repair Clearcoat                                   | F8200 or F8201                         | F8311                        | 3 : 1 : 1                                  | 1.36 (163)                               |
| F8600 Ultra Low VOC Repair Clearcoat                                   | F8200 or F8201                         | F8314                        | 3 : 1 : 1                                  | 1.89 (226)                               |
| F8605 Ultra Low VOC Clearcoat  | F8200 or F8201                         | F8311                        | 3 : 1 : 1                                  | 1.51 (181)                               |
| F8605 Ultra Low VOC Clearcoat  | F8200 or F8201                         | F8314                        | 3 : 1 : 1                                  | 2.01 (241)                               |
| <b>Additional Products: (listing not intended to be all inclusive)</b> |  |                              |  |  |
| F8720 Blending Clear   | SU4901 Clean and Scuff Sponge          |                              | SXA840 Uniform Finish Blender<br>(Aerosol) |  |
| SLV840 Uniform Finish Blender  | SU470LV 1K Compliant Adhesion Promoter |                              |  |  |

**San Joaquin Valley Unified APCD Rule 4612 – PPG DELFLEET ONE™**

This "San Joaquin Valley Unified APCD Rule 4612 (PPG Delfleet One)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "San Joaquin Valley APCD Rule 4612 (PPG Delfleet One)" wall chart does not include all currently compliant Delfleet One products. The representative products listed are compliant with Rule 4612 VOC limits as of the date of this wall chart; however, subsequent changes in Rule 4612 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.



PPG Industries  
 Commercial Coatings  
 19699 Progress Drive  
 Strongsville, OH 44149  
 1-800-647-6050

PPG Canada Inc.  
 2301 Royal Windsor Drive, Unit #6  
 Mississauga, Ontario L5J 1K5  
 1-888-310-4762